

sunlite[®]

Providing All of Your Lighting Needs Since 1980



2024

FIXTURE CATALOG

ABOUT US

For over 40 years Sunshine Lighting has been providing quality and affordable solutions to the lighting industry and has evolved into a multinational enterprise, growing at a rapid pace to become a leading lighting manufacturer in North America. Sunshine Lighting offers a wide array of products under multiple brands including MKS LED®, Ambiate® and Sunlite® lamps and luminaires. We take great pride in maintaining a personal relationship with each customer. Sunshine Lighting has gained a reputation for quality and affordability while keeping up with the latest technologies.

The Sunlite® brand was introduced in 1996 to provide select lighting technologies consisting of Indoor, Industrial and Outdoor LED and Non-LED fixtures, as well as LED, Compact Fluorescent, HID, Halogen, Decorative, Miniature, Specialty, Stage and Studio lamps. Our dedicated team of technical and product specialists ensures that our products designed with safety and the environment in mind. Most products carry the Underwriters Laboratories (UL), Intertek's ETL Listing, Department of Energy (DOE) Energy Star certifications, Design Lights Consortium (DLC) qualified products listing, and/or the American Lighting Association (ALA) among others.

Through customer interaction and feedback, we introduce new and innovative products to the marketplace as well as continually improving our existing line of items to meet the high expectations our customers have come to rely on us. In addition, we provide exclusive service to customers whether it's a product tweak, modification, or full custom product, Sunshine Lighting's dedicated engineering and project management team is ready assist.

sunlite®

Copyright ©2024 Sunlite

For Product inquiries or to place an order, please contact us at:

TOLL FREE PHONE: 800.605. BULB

VISIT: www.sunlite.com

For general information and request a catalog: info@sunshinelighting.com

Sales department: sales@sunshinelighting.com

Terms & Conditions <https://sunlite.com/terms-of-use>

NYC Warehouse
744 Clinton Street
Brooklyn, NY 11231
Tel: 718.768.7000
Fax: 718.768.0970

TABLE OF CONTENTS

Linear Ceiling Flush Mount	4 - 7
Linear Bed Light	8
Under Cabinet	8 - 9
Linear Shop Light	9
Ceiling Flat Panel & Kits	10
Recessed Troffer	11
Recessed Ceiling	11
Downlight	12 - 18
Downlight Retrofit	18 - 19
Pendant Fixture	20 - 27
Ceiling Flush Mount	27 - 42
Adjustable Track Light	43
Wall Mount Sconce	44-56
Outdoor Wall Sconce	58-68
Outdoor Post Mounted Fixture	69-70
Outdoor Wall Sconce	70 -72
Outdoor Wall Mount Fixture	73-74
Outdoor Gooseneck Fixture	75
Outdoor Security Flood Light	76
Outdoor Post Mounted Fixture	77
Outdoor Ceiling Flush Mount	77
Outdoor Wall Mount	78 -81
Outdoor Floodlight	81
Outdoor Pole-Top Area Light	82 - 83
Outdoor Parking Garage Canopy Light	84
Bollard Garden Pathway Series	84
Commercial UFO High Bay	85
Commercial Linear High Bay	86
Commercial Pendants High Bay	87
High Lumen Lamp	87
VaporProof Light	88
Construction Work Light	89 - 90
String Lights	90 - 91
Emergency Light	91
Exit Sign & Emergency Lights Combo	92
Exit Sign	93 - 94
Flush Mount Circular Module Retrofit Kit	95
Bezel Lights	96
Step Light	97
Refrigerator Display Strip	97
Replacement Lenses	98 - 99



LED Linear Ceiling Flush Mount

Linear Strip Light Fixture



The ability to open the fixture without any tools can be a time-saving and convenient feature, especially during installation or maintenance.

Metal & Acrylic Body
White Lens
White Finish
80 CRI

Options



Application



Components

85639-SU	SF/BLS/LN/RMT	Remote for Motion Sensor
85637-SU	SF/PC/LN/1W	Photocell Sensor
85636-SU	SF/ST/LN/SK	5Ft Suspension Kit
85638-SU	SF/ST/LN/CB	Corner Mounting Bracket
85635-SU	SF/ST/LN/EB	End to End Bracket




Optional For Battery Backup & Motion Sensor



Remote for Motion Sensor



Photocell Sensor



5Ft Suspension Kit



Corner Mounting Bracket



End to End Bracket

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
2FT, 4FT, and 8FT								
85620-SU	SF/ST/LN/24/MW/83S/MV/WH	15/20/25	2060/2742/3167	120-277	35K/40K/50K	50000	DL,DIM,DLC	2.65(h) 2.60(w) 23.95(d)
85624-SU	SF/ST/LN/48/MW/83S/MV/WH	28/35/40	3877/4702/5287	120-277	35K/40K/50K	50000	DL,DIM,DLC	2.65(h) 2.60(w) 47.55(d)
85628-SU	SF/ST/LN/96/MW/83S/MV/WH	30/45/60	4329/6435/8560	120-277	35K/40K/50K	50000	DL,DIM,DLC	2.65(h) 2.60(w) 94.80(d)
Built-in Photocell & Bi-Level Sensor								
85621-SU	SF/ST/LN/24/MW/83S/MV/WH/BLS	15/20/25	2060/2742/3167	120-277	35K/40K/50K	50000	DL,DIM,DLC	2.65(h) 2.60(w) 23.95(d)
85625-SU	SF/ST/LN/48/MW/83S/MV/WH/BLS	28/35/40	3877/4702/5287	120-277	35K/40K/50K	50000	DL,DIM,DLC	2.65(h) 2.60(w) 47.55(d)
85629-SU	SF/ST/LN/96/MW/83S/MV/WH/BLS	30/45/60	4329/6435/8560	120-277	35K/40K/50K	50000	DL,DIM,DLC	2.65(h) 2.60(w) 94.80(d)
Built-in 90-Min. Emergency Backup Battery								
85622-SU	SF/ST/LN/24/MW/83S/MV/WH/EM	15/20/25	2060/2742/3167	120-277	35K/40K/50K	50000	DL,DIM,DLC	2.65(h) 2.60(w) 23.95(d)
85626-SU	SF/ST/LN/48/MW/83S/MV/WH/EM	28/35/40	3877/4702/5287	120-277	35K/40K/50K	50000	DL,DIM,DLC	2.65(h) 2.60(w) 47.55(d)
85630-SU	SF/ST/LN/96/MW/83S/MV/WH/EM	30/45/60	4329/6435/8560	120-277	35K/40K/50K	50000	DL,DIM,DLC	2.65(h) 2.60(w) 94.80(d)
Built-in 90-Min. Emergency Backup Battery Photocell & Bi-Level Sensor								
85623-SU	SF/ST/LN/24/MW/83S/MV/WH/BLS/EM	15/20/25	2060/2742/3167	120-277	35K/40K/50K	50000	DL,DIM,DLC	2.65(h) 2.60(w) 23.95(d)
85627-SU	SF/ST/LN/48/MW/83S/MV/WH/BLS/EM	28/35/40	3877/4702/5287	120-277	35K/40K/50K	50000	DL,DIM,DLC	2.65(h) 2.60(w) 47.55(d)
85631-SU	SF/ST/LN/96/MW/83S/MV/WH/BLS/EM	30/45/60	4329/6435/8560	120-277	35K/40K/50K	50000	DL,DIM,DLC	2.65(h) 2.60(w) 94.80(d)

Metal & Acrylic Body
White Lens
White Finish
82 CRI

Options

5 Year Warranty | Battery Backup | Motion Sensor

Application

Education | Medical | Industrial | Commercial | Residential



Suspension Kit




Optional For Battery Backup & Motion Sensor

Components
 85364-SU Suspension Kit

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	2.4" Linear Strip Fixture 2 Foot Built-in 90-Min. Emergency Backup Battery Bi-Level Sensor							
85464-SU	LFX/EC/2'/MW/4SCT/EM	15/20/25	3250	120-277	30K/35K/40K/50K	50000	DL,DIM	2.4(h) 3.35(w) 23.6(d)
B	3.6" Linear Strip Fixture 2 Foot							
85471-SU	LFX/EC/2'/20W/MV/D/40K	20	2620	120-277	4000K	50000	DL,DIM,DLC	3.6(h) 3.3(w) 22.2(d)

LED Linear Ceiling Flush Mount

Linear Strip Light Fixture



LED BUILT-IN

SWITCH
Color Selectable

SWITCH
Power Selectable

Metal & Plastic Body
White Lens
White Finish
80 CRI

Options

3 Year Warranty | Battery Backup

Application


Education | Medical | Industrial | Commercial | Residential



Optional For Battery Backup & Motion Sensor

LED Linear Ceiling Flush Mount

Slim Linear Strip Light Fixture



LED BUILT-IN

SWITCH
Color Selectable

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
2 Foot-1 Light								
85550-SU	LFX/ST/2FT/1L/10W/SCT	10	1150	120-277	30K/40K/50K	50000	DL,DIM,DLC	2.4(h) 2.1(w) 24.0(d)
2 Foot-2 Light (Emergency Backup Optional)								
85552-SU	LFX/ST/2FT/2L/20W/SCT	20	2300	120-277	30K/40K/50K	50000	DL,DIM,DLC	2.4(h) 3.8(w) 24.0(d)
4 Foot-1 Light								
85551-SU	LFX/ST/4FT/1L/20W/SCT	20	2300	120-277	30K/40K/50K	50000	DL,DIM,DLC	2.4(h) 2.1(w) 48.0(d)
85403-SU	LFX/ST/4FT/1L/15W/30K	15	1900	120-277	3000K	50000	DL,DIM,DLC	2.2(h) 1.8(w) 48.0(d)
85404-SU	LFX/ST/4FT/1L/15W/40K	15	1950	120-277	4000K	50000	DL,DIM,DLC	2.2(h) 1.8(w) 48.0(d)
4 Foot-2 Light (Emergency Backup Optional)								
85553-SU	LFX/ST/4FT/2L/40W/SCT	40	4600	120-277	30K/40K/50K	50000	DL,DIM	2.4(h) 3.8(w) 48.0(d)



Metal & Plastic Body
Clear Lens
White Finish
80 CRI

Options



- 5 Year Warranty
- Battery Backup
- Motion Sensor

Application


- Education
- Medical
- Industrial
- Commercial
- Residential

LED Linear Ceiling Flush Mount

Premium Wrap Around



A



B



Optional For Battery Backup & Motion Sensor

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	7.75"							
85292-SU	LFX/WA7/4'/MW/SCT	30/35/40	5000	120	35k/40K/50K	50000	DL,DIM,DLC	2.8(h) 7.08(w) 47.72(d)
Built-in Sensor & Battery Backup								
90721-SU	LFX/WA7/4'/MW/SCT/EM	30/35/40	5000	120	35k/40K/50K	50000	DL,DIM,DLC	2.8(h) 7.08(w) 47.72(d)
90722-SU	LFX/WA7/4'/MW/SCT/BLS	30/35/40	5000	120	35k/40K/50K	50000	DL,DIM,DLC	2.8(h) 7.08(w) 47.72(d)
90723-SU	LFX/WA7/4'/MW/SCT/EM/BLS	30/35/40	5000	120	35k/40K/50K	50000	DL,DIM,DLC	2.8(h) 7.08(w) 47.72(d)
B	9.75"							
85290-SU	LFX/WA9/4'/40W/40K	40	5200	120	4000K	50000	DL,DIM	2.2(h) 9.7(w) 48.0(d)

Steel Body
PMMA White Lens
White Finish
80 CRI

Options


- 5 Year Warranty
- Battery Backup

Application

- Education
- Medical
- Industrial
- Commercial
- Residential

LED Linear Ceiling Flush Mount

Design Wrap Around



Optional For Battery Backup & Motion Sensor

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
85298-SU	LFX/WA5/4'/3MW/3SCT	32/40/48	3680/4600/5520	120-277	35K/40K/50K	50000	DL,DIM	2.1(h) 5.3(w) 47.6(d)
85291-SU	LFX/WA5/4'/48W/40K	48	5520	120-277	4000K	50000	DL,DIM	2.1(h) 5.3(w) 47.6(d)

Steel Body
White Lens
White Finish
80 CRI

Options

5 Year Warranty

Battery Backup

Motion Sensor

Application

Industrial Commercial

LED Linear Ceiling Flush / Wall Mount

Stairway



Optional For Battery Backup & Motion Sensor

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
2FT, 3FT, and 4FT Length								
82115-SU	SF/WR4/LN/24/MW/93S/MV/WH	10/15/18	1150/1725/2070	120-277	30K/40K/50K	50000	DL,DIM	3.25(h) 24.3(w) 4.3(d)
82119-SU	SF/WR4/LN/36/MW/93S/MV/WH	18/25/30	2070/2875/3450	120-277	30K/40K/50K	50000	DL,DIM	3.25(h) 36.0(w) 4.3(d)
82123-SU	SF/WR4/LN/48/MW/93S/MV/WH	20/28/36	2300/3220/4140	120-277	30K/40K/50K	50000	DL,DIM	3.25(h) 48.35(w) 4.3(d)
Emergency Backup 2FT, 3FT, and 4FT Length								
82117-SU	SF/WR4/LN/24/MW/93S/MV/WH/EM	10/15/18	1150/1725/2070	120-277	30K/40K/50K	50000	DL,DIM	3.25(h) 24.3(w) 4.3(d)
82121-SU	SF/WR4/LN/36/MW/93S/MV/WH/EM	18/25/30	2070/2875/3450	120-277	30K/40K/50K	50000	DL,DIM	3.25(h) 36.0(w) 4.3(d)
82125-SU	SF/WR4/LN/48/MW/93S/MV/WH/EM	20/28/36	2300/3220/4140	120-277	30K/40K/50K	50000	DL,DIM	3.25(h) 48.35(w) 4.3(d)
Bi-Level Sensor 2FT, 3FT, and 4FT Length								
82116-SU	SF/WR4/LN/24/MW/93S/MV/WH/BLS	10/15/18	1150/1725/2070	120-277	30K/40K/50K	50000	DL,DIM	3.25(h) 24.3(w) 4.3(d)
82120-SU	SF/WR4/LN/36/MW/93S/MV/WH/BLS	18/25/30	2070/2875/3450	120-277	30K/40K/50K	50000	DL,DIM	3.25(h) 36.0(w) 4.3(d)
82124-SU	SF/WR4/LN/48/MW/93S/MV/WH/BLS	20/28/36	2300/3220/4140	120-277	30K/40K/50K	50000	DL,DIM	3.25(h) 48.35(w) 4.3(d)
Emergency Backup Bi-Level Sensor 2FT, 3FT, and 4FT Length								
82118-SU	SF/WR4/LN/24/MW/93S/MV/WH/BLS/EM	10/15/18	1150/1725/2070	120-277	30K/40K/50K	50000	DL,DIM	3.25(h) 24.3(w) 4.3(d)
82122-SU	SF/WR4/LN/36/MW/93S/MV/WH/BLS/EM	18/25/30	2070/2875/3450	120-277	30K/40K/50K	50000	DL,DIM	3.25(h) 36.0(w) 4.3(d)
82126-SU	SF/WR4/LN/48/MW/93S/MV/WH/BLS/EM	20/28/36	2300/3220/4140	120-277	30K/40K/50K	50000	DL,DIM	3.25(h) 48.35(w) 4.3(d)

Polycarbonate Body
White Lens
White Finish
80 CRI

Options

5 Year Warranty

Battery Backup




Motion Sensor

Application

Education Medical Industrial Commercial Residential

LED Linear Ceiling Flush Mount

Vapor Tight Strip



Optional For Battery Backup & Motion Sensor

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
4FT, and 8FT Length								
85260-SU	LFX/VTS/4'/3MW/3SCT	25/38/50	3500/5400/7000	120-277	35K/40K/50K	50000	WL,DIM,DLC	3.42(h) 49.7(w) 3.34(d)
85261-SU	LFX/VTS/8'/3MW/3SCT	72/80/100	9800/11000/13500	120-277	35K/40K/50K	50000	WL,DIM,DLC	4.13(h) 96.0(w)4.33(d)
Built-in Sensor & Battery Backup								
90735-SU	LFX/VTS/4'/MW/3SCT/EM	25/38/50	3500/5400/7000	120-277	35K/40K/50K	50000	WL,DIM,DLC	3.42(h) 49.7(w) 3.34(d)
90737-SU	LFX/VTS/4'/MW/3SCT/EM/BLS	25/38/50	3500/5400/7000	120-277	35K/40K/50K	50000	WL,DIM,DLC	3.42(h) 49.7(w) 3.34(d)
90745-SU	LFX/VTS/8'/3MW/3SCT/EM	72/80/100	9800/11000/13500	120-277	35K/40K/50K	50000	WL,DIM,DLC	4.13(h) 96.0(w)4.33(d)
85265-SU	LFX/VTS/8'/3MW/3SCT/BLS	72/80/100	9800/11000/13500	120-277	35K/40K/50K	50000	WL,DIM,DLC	4.13(h) 96.0(w)4.33(d)



Aluminum & Plastic Body
White Lens
White Finish
80 CRI

Options

5 Year Warranty

Battery Backup

Application: Education, Medical

LED Linear Bed Light

Hospital Series

LED
BUILT-IN

Sunlite Lighting's LED overbed lights are fabricated with your patient and medical staff in mind. This light bar creates a potent, but comfortable ENVIRONMENT that avoids disrupting others nearby, while providing enough light to read medical records, books and maneuver around during all hours in the day.



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
36" Length								
49189-SU	SF/BL/LN/36/45/83S/120/WH	15/30/45	1794/3590/5311	120	30K/40K/50K	50000	DL,DIM,DLC	4.06(h) 4.22(w) 36(d)
48" Length								
49190-SU	SF/BL/LN/48/60/83S/120/WH	20/40/60	2348/4697/6958	120	30K/40K/50K	50000	DL,DIM,DLC	4.06(h) 4.22(w) 48.0(d)

Sunlite Linkable LED Under Cabinet Fixtures are an energy efficient lighting solution for kitchens, bathrooms, offices, workbenches, and more. Fixtures can be linked together directly with built-in male/female connectors. Or use the included connector cord to space them further apart. Each fixture has an on/off switch so they can be operated independently and includes mounting hardware, and a 5-foot power cord that plugs into any standard 120 volt outlet.

Plastic Body
White Lens
White Finish
80 CRI

2 Year Warranty

Application: Office, Commercial, Residential

LED Under Cabinet

Linkable (Plug-In)

LED
BUILT-IN



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
12" Length								
53107-SU	LFX/UC/12"/5W/SCT	5	500	120	30K/40K/50K	50000	DL	1.2(h) 0.9(w) 12.3(d)
53071-SU	LFX/UC/12/4W/30K	4	320	120	3000K	35000	DL	1.2(h) 0.9(w) 12.3(d)
22" Length								
53108-SU	LFX/UC/22"/9W/SCT	9	900	120	30K/40K/50K	50000	DL	1.2(h) 0.9(w) 22.6(d)
34" Length								
53109-SU	LFX/UC/34"/12W/SCT	12	1200	120	30K/40K/50K	50000	DL	1.2(h) 0.9(w) 34.4(d)
46" Length								
53110-SU	LFX/UC/46"/16W/SCT	16	1600	120	30K/40K/50K	50000	DL	1.2(h) 0.9(w) 46.2(d)

Plastic Body
White Lens
White Finish
80 CRI

3
Year
Warranty

Application



LED Under Cabinet

Linkable (Plug-In)

LED
BUILT-IN



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
12", 20", and 40" Length								
88616-SU	LFX/UCF/12/40K	5	300	24	4000K	50000	DL,DIM	12 (w)
88619-SU	LFX/UCF/20/30K	8	480	24	3000K	50000	DL,DIM	20 (w)
88620-SU	LFX/UCF/20/40K	8	480	24	4000K	50000	DL,DIM	20 (w)
88623-SU	LFX/UCF/40/30K	15	900	24	3000K	50000	DL,DIM	40 (w)
88624-SU	LFX/UCF/40/40K	15	900	24	4000K	50000	DL,DIM	40 (w)

Metal & Acrylic Body
White Lens
White Finish
90 CRI

5
Year
Warranty

Application



LED Under Cabinet

Linkable (Hard Wire)

LED
BUILT-IN



Connector

53075-SU Connector



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
18" Length Color Selectable								
53079-SU	LFX/UC/10W/18"/90CRI/SCT/WH	10	600	120	30K/40K/50K	50000	DL,DIM	1.0(h) 3.7(w) 18.1(d)

Metal & Plastic Body
White Lens
White Finish
80 CRI

5
Year
Warranty

Application



LED Linear Shop Light

Chain Suspension

LED
BUILT-IN



Aircraft Cable

85416-SU AC/LFX/ST/3'/2PK



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
Indoor Linkable								
85415-SU	LFX/ST/T8/4FT/32W/950	32	4800	100-277	5000K	50000	DL	1.4(h) 1.2 (w) 47.4(d)



LED Ceiling Flat Panel & Kits

Backlit & Edge Lit



2' x 2'



1' x 4'




2' x 4'

Aluminum Body
White Lens
PMMA Optical Lens
White Finish
80 CRI

Options



Application



PMMA Optical Lens Will Not Turn Yellow Over Time



Optional For Battery Backup & Motion Sensor

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
Backlit								
85640-SU	SF/BLI/FP/14/MW/83S/MV/WH/2PK	20/30/40	2500/3750/5000	120-277	35K/40K/50K	50000	DL,DIM,DLC	1.4(h) 47.8(w) 11.9(d)
85641-SU	SF/BLI/FP/22/MW/83S/MV/WH/2PK	20/30/40	2500/3750/5000	100-277	35K/40K/50K	50000	DL,DIM,DLC	1.4(h) 23.7(w) 23.7(d)
85642-SU	SF/BLI/FP/24/MW/83S/MV/WH/2PK	30/40/50	3750/5000/6250	100-277	35K/40K/50K	50000	DL,DIM,DLC	1.4(h) 47.8(w) 23.7(d)
85612-SU	LFX/2X4/B-L/3MW/3SCT/V2/4PK	30/40/50	3300/4400/5500	100-277	35K/40K/50K	50000	DL,DIM,DLC	1.5(h) 47.8(w) 23.7(d)
Edge Lit								
85380-SU	LFX/2X4/60W/30K/D/MV/0-10V/2PK	60	6000	100-277	3000K	50000	DL,DIM,DLC	0.4(h) 23.8(w) 47.8(d)

Surface Mount

- 85146-SU LFX/FLAT/1X4
- 85148-SU LFX/FLAT/2X2
- 85149-SU LFX/FLAT/2X4



Sheetrock Recessed Mounting

- 85087-SU LFX/FLAT/1X4/RECESED
- 85090-SU LFX/FLAT/2X2/RECESED
- 85091-SU LFX/FLAT/2X4/RECESED










Suspension Kit

- 85124-SU LFX/FLAT/2X2/1X4
- 85129-SU LFX/FLAT/2X4



Aluminum Body
White Lens
White Finish
80 CRI

Options
5 Year Warranty
 Battery Backup

Application       

LED Recessed Troffer

Center Basket



Sheetrock Recessed Mounting

- 85138-SU LFX/FLAT/2X2
- 85139-SU LFX/FLAT/2X4



Optional For Battery Backup
& Motion Sensor

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
2X4 Option								
85229-SU	LFX/2X4/55W/D/MV/40K	55	7040	120-277	4000K	50000	DL,DIM,DLC	48.0(h) 24.0(w) 2.8(d)
Color Selectable								
85214-SU	LFX/2X2/SCT/MW/MV/D	20/25/30	2640/3250/3750	120-277	35K/40K/50K	50000	DL,DIM,DLC	2.8(h) 23.8(w) 23.8(d)
85215-SU	LFX/2X4/SCT/MW/MV/2PK	25/30/34	3350/3900/4285	120-277	35K/40K/50K	50000	DL,DIM,DLC	2.8(h) 23.8(w) 47.8(d)



LED Recessed Ceiling








Flat T-Grid Lighting System





Sunlite's T-Grid Lighting System is an innovative lighting solution designed to replace 9/16" and 15/16" grid supports allowing seamless integration into your suspended drop ceiling. Create interesting and decorative designs with custom patterns such as an L-shape, T-shape, plus signs, outlined squares, and more.

Aluminum & Pc Body
White Lens
Matte Silver Finish
80 CRI

5 Year Warranty

Application       



Drivers (Required)

88797-SU	TGRID/DRIVER/30W
88798-SU	TGRID/DRIVER/60W


Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
2 Foot								
88786-SU	LFX/TGRID/2FT/D/10W/35K/14mm	10	1100	100-277	3500K	50000	DIM	24.0(h) 0.6(w) 0.5(d)
88789-SU	LFX/TGRID/2FT/D/10W/35K/24mm	10	1300	100-277	3500K	50000	DIM	24.0(h) 0.9(w) 0.5(d)
4 Foot								
88784-SU	LFX/TGRID/4FT/D/20W/30K/24mm	20	2400	100-277	3000K	50000	DIM	48.0(h) 0.6(w) 0.5(d)

Specifications may change without notice.
 We are not responsible for any typographical errors

LED Recessed Remodel / New Construction Canless Downlight

Ultra Slim Wafer Downlights

These ultra slim downlights from Sunlite feature innovative technology that provides down lighting without all the labor. Use for new installations or as a retrofit replacement for existing recessed lighting. Perfect for residential, commercial, retail, office, hospitality and educational institutions. These dimmable fixtures are instant on with no warmup time. And no flickering or buzzing like fluorescent bulbs. They are ETL Listed for damp location installation and Energy Star Certified.



Aluminum & Acrylic Body
White Lens
White Finish
80 / 90 CRI

5 Year Warranty **IC** Rated

Application

- Education
- Hospitality
- Office
- Retail
- Commercial
- Residential



A



B




C



D

Suitable Tight Space Installation (NO HOUSING NEEDED)



New Construction Mounting Option

- 87705-SU Construction Plate
- 87726-SU Construction Plate



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A Round Color Selectable 90 CRI Available 4", 6", and 8"								
87800-SU	LFX/SDL/4R/12W/90CRI/5SCT	12	700	120	27K/30K/35K/40K/50K	50000	WL,DIM	1.0(h) 4.93(d)
87707-SU	LFX/SDL/6R/12W/90CRI/5SCT	12	950	120	27K/30K/35K/40K/50K	35000	WL,DIM	1.0(h) 6.8(d)
87801-SU	LFX/SDL/6R/14W/90CRI/5SCT	14	1000	120	27K/30K/35K/40K/50K	50000	WL,DIM	1.0(h) 6.8(d)
87804-SU	LFX/SDL/8R/18W/90CRI/5SCT	18	1100	120	27K/30K/35K/40K/50K	50000	WL,DIM	1.0(h) 8.85(d)
B Square Color Selectable 90 CRI Available 4" and 6"								
87708-SU	LFX/SDL/4S/10W/SCT	10	700	120	27K/30K/35K/40K/50K	35000	DL,DIM,ES	0.78(h) 4.8(w)
87802-SU	LFX/SDL/4S/12W/90CRI/5SCT	12	800	120	27K/30K/35K/40K/50K	30000	WL,DIM,ES	1.0(h) 4.8(w)
87709-SU	LFX/SDL/6S/12W/SCT	12	950	120	27K/30K/35K/40K/50K	35000	DL,DIM,ES	0.87(h) 6.8(w)
C Square 80 CRI								
82057-SU	LFX/SDL/4S/10W/D/E/50K	10	650	120	5000K	36000	DL,DIM,ES	0.8(h) 4.7(w)
D Square Black								
87805-SU	LFX/SDL/4S/12W/90CRI/5SCT/BK	10	800	120	27K/30K/35K/40K/50K	35000	WL,DIM,ES	0.78(h) 4.8(w)

LED Recessed Remodel / New Construction Canless Downlight

Regressed Gimbal





The canless LED recessed light with a 360° rotatable “eyeball” and 15° tilt is a versatile and modern lighting solution that allows you to easily adjust the direction of your lighting to suit your needs. The absence of a recessed can in the design makes installation a breeze, and the included junction box, plug and twist connection, and spring loaded clips ensure a simple and secure installation with a flush finish to your ceiling. This type of LED light fixture is a great option for anyone who wants to upgrade their lighting with a product that provides greater control and flexibility over the direction and intensity of their lighting, while also being easy to install.



Aluminum & Acrylic Body
White Lens
White Finish
90 CRI



Application



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	85607-SU LFX/GDL/3.5R/12W/90CRI/5SCT	12	825	120	27K/30K/35K/40K/50K	50000	WL,DIM,ES	(W) 4.38 (H) 3.25 (D) 4.38
B	85608-SU LFX/GDL/2L/3.5R/24W/90CRI/5SCT	24	1540	120	27K/30K/35K/40K/50K	50000	WL,DIM,ES	(W) 7.88 (H) 3.25 (D) 4.38
C	85609-SU LFX/GDL/3L/3.5R/36W/90CRI/5SCT	36	2270	120	27K/30K/35K/40K/50K	50000	WL,DIM,ES	(W) 11.68 (H) 3.25 (D) 4.38

Specifications may change without notice.
We are not responsible for any typographical errors

SUNLITE.COM

CALL 718.768.7000 TOLL-FREE 800.605.BULB

sunlite

LED Recessed Remodel / New Construction Canless Downlight

Interchangeable Trims Regressed Downlight

LED recessed lighting is a versatile and convenient lighting option for any space, whether you are doing a home remodel or working with new construction. This canless downlight is designed to be an all-in-one solution that is quick, easy to install, and offers customizable color options. With five color options, 27K/30K/35K/40K/50K. Each recessed ceiling light has a junction box with quick connectors for simple wiring. The included interchangeable trim features a twist lock application that is easy to change the trim style in the future. In addition, with the ability to dim from 100% to 10%, you can control the light output according to your mood and preferences. Moreover, the wet location rating makes the LED recessed lighting suitable for outdoor and bathroom environments where moisture may be present. The LED recessed lighting is built to last, with an astounding 50,000-hour lifetime.



A



B



C

Aluminum & Acrylic Body
White Lens
White Finish
90 CRI




Application



Trim for 85589-SU		Trim
85592-SU	TRIM/DAD/2R/BK	2" Black Round
85593-SU	TRIM/DAD/2R/BN	2" Brushed Nickel Round
85594-SU	TRIM/DAD/2S/WH	2" White Square
85595-SU	TRIM/DAD/2S/BK	2" Black Square
85596-SU	TRIM/DAD/2S/BN	2" Brushed Nickel Square

Trim for 85590-SU		Trim
85597-SU	TRIM/DAD/4R/BK	4" Black Round
85598-SU	TRIM/DAD/4R/BN	4" Brushed Nickel Round
85599-SU	TRIM/DAD/4S/WH	4" White Square
85600-SU	TRIM/DAD/4S/BK	4" Black Square
85601-SU	TRIM/DAD/4S/BN	4" Brushed Nickel Square

Trim for 85591-SU		Trim
85602-SU	TRIM/DAD/6R/BK	6" Black Round
85603-SU	TRIM/DAD/6R/BN	6" Brushed Nickel Round
85604-SU	TRIM/DAD/6S/WH	6" White Square
85605-SU	TRIM/DAD/6S/BK	6" Black Square
85606-SU	TRIM/DAD/6S/BN	6" Brushed Nickel Square




Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	85589-SU LFX/DAD/2R/15W/90CRI/5SCT/WH	15	1055	120	27K/30K/35K/40K/50K	50000	WL,DIM,ES	(H) 4.92 (D) 3.13
B	85590-SU LFX/DAD/4R/18W/90CRI/5SCT/WH	18	1360	120	27K/30K/35K/40K/50K	50000	WL,DIM,ES	(H) 4.8 (D) 4.5
C	85591-SU LFX/DAD/6R/24W/90CRI/5SCT/WH	24	1735	120	27K/30K/35K/40K/50K	50000	WL,DIM,ES	(H) 2.95 (D) 7.3



Aluminum & Acrylic Body
White Lens
White Finish
92 CRI

5 Year Warranty
IC Rated



LED Recessed Remodel / New Construction Canless Downlight

Regressed Anti-Glare



Round

Square



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
4" Round								
85564-SU	LFX/DAD/4R/90CRI/12W/3SCT	12	900	120	30K/40K/50K	35000	DL,DIM	4.18(h) 4.8(d)
4" Square								
85565-SU	LFX/DAD/4S/90CRI/12W/3SCT	12	900	120	30K/40K/50K	35 000	DL,DIM	3.0(w) 6.5(w)

Aluminum Body
White Lens
White Finish
80 CRI

Options
5 Year Warranty
IC Rated
Battery Backup

Application

LED Recessed Remodel / New Construction Canless Downlight

ALLIE



A Canless Version

The days of stocking many products to accommodate various color temperature options are over. Meet Allie! The All In One Downlight that you can stock with 3 built-in color temperatures.



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	87717-MKS MKS/MDL/ALLIE/4R/CCT	20	1500	120-277	30K/40K/55K	50000	DIM,ES	1.75 (h) 4.75(d)
B	87713-MKS MKS/NDL/ALLIE/4R/CCT	20	1500	120-277	30K/40K/55K	50000	DIM,ES	13.8 (h) 11.5(w) 4.0(d)

Sunlite's Direct to Junction Box downlight series can be installed directly into a standard ceiling junction box (or deep j-box for regressed version) or as a retrofit in existing recessed cans using the included hardware. With the innovative magnetic interchangeable trims, choosing a finish couldn't be simpler.

Aluminum Body
Frosted Glass Lens
White Finish
90 CRI

5 Year Warranty
IC Rated

Application




LED Direct to Junction Box downlight

Direct to Junction Box



Retrofit hardware included for directly into recessed cans



Item#		Trim
87695-SU	SF/DTR/RD/4/BK	4" Black Trim
87696-SU	SF/DTR/RD/4/SL	4" Silver Trim

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A Round Regressed Lens								
87691-SU	SF/DRL/RD/4/13/927/120/WH	13	1050	120	2700K	50000	DL,DIM	1.4(h) 4.85(w)
87692-SU	SF/DRL/RD/4/13/930/120/WH	13	1050	120	3000K	50000	DL,DIM	1.4(h) 4.85(w)
87693-SU	SF/DRL/RD/4/13/935/120/WH	13	1050	120	3500K	50000	DL,DIM	1.4(h) 4.85(w)
87694-SU	SF/DRL/RD/4/13/940/120/WH	13	1050	120	4000K	50000	DL,DIM	1.4(h) 4.85(w)
B Round Flat Lens								
87688-SU	SF/DFL/RD/4/10/927/120/WH	10	900	120	2700K	50000	DL,DIM	1.0(h) 4.85(w)
87689-SU	SF/DFL/RD/4/10/930/120/WH	10	900	120	3000K	50000	DL,DIM	1.0(h) 4.85(w)
87690-SU	SF/DFL/RD/4/10/940/120/WH	10	900	120	4000K	50000	DL,DIM	1.0(h) 4.85(w)

Aluminum & Plastic Body
White Lens
White Finish
80 CRI



Application



LED Recessed New Construction J-Box Downlight

Recessed Clip On Installation



Item#	Trim
50116-SU	TRIM/4R/BR 4" Bronze Trim
50117-SU	TRIM/4R/BL 4" Black Trim
50118-SU	TRIM/6R/BR 6" Bronze Trim
50119-SU	TRIM/6R/BL 6" Black Trim

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
4" Round								
89930-SU	LFX/JDL/BF/4R/10W/E/D/30K	10	600	120	3000K	50000	WL,DIM,ES	3.7(w) 5.0(d)
6" Round								
89936-SU	LFX/JDL/BF/6R/15W/E/D/30K	15	1000	120	3000K	50000	WL,DIM,ES	3.0(w) 7.3(d)
89937-SU	LFX/JDL/BF/6R/15W/E/D/40K	15	1020	120	4000K	50000	WL,DIM,ES	3.0(w) 7.3(d)

Replace your 6-inch round recessed can lighting with these commercial grade, high-output LED fixtures from Sunlite. The aluminum body features a white finish and wires directly into your existing junction box. They are dimmable (100%-10%) and employ spring loaded tabs for easy installation into your existing light openings. ETL Listed for damp location installation. With no bulbs to replace and long 50,000 hour life span these are the perfect no-maintenance solution. Ideal for showrooms, retail locations, ballrooms, meeting spaces, atriums, entryways, hallways, or anywhere bright down lighting is needed.

LED Recessed Commercial Retrofit Downlight

Recessed Clip On Installation



Aluminum & PC Body
White Lens
White Finish
90 / 80 CRI

Options



Application



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
90 CRI Damp Location Rated								
87808-SU	LFX/CRD/4R/90CRI/3MW/5SCT/V2	9/13/18	1000/1500/2000	120-347	27K/30K/35K/40K/50K	50000	DL,DIM,ES	4.0(h) 5.9(d)
87809-SU	LFX/CRD/6R/90CRI/3MW/5SCT/V2	13/19/27	1500/2100/3000	120-347	27K/30K/35K/40K/50K	50000	DL,DIM,ES	4.4(h) 8.25(d)
87810-SU	LFX/CRD/8R/90CRI/3MW/5SCT/V2	18/27/36	2000/3000/4000	120-347	27K/30K/35K/40K/50K	50000	DL,DIM,ES	4.75(h) 10.25(d)
87811-SU	LFX/CRD/9.5R/90CRI/3MW/5SCT/V2	20/30/40	2500/3750/5000	120-347	27K/30K/35K/40K/50K	50000	DL,DIM,ES	4.75(h) 11.2(d)
Wet Location Rated								
87732-SU	LFX/CRD/SCT/6R/MW/D/6"	9/13/19	750/1050/1500	120-277	30K/35K/40K	50000	WL,DIM,ES	4.5(h) 8.4(d)
Wet Location Rated Emergency Backup Compatible								
87736-SU	LFX/CRD/SCT/8R/33W/8"/EM	33	3000	120-277	30K/35K/40K/50K	50000	WL,DIM,ES	5.2(h) 10.0(d)
87737-SU	LFX/CRD/SCT/8R/55W/8"/EM	55	5000	120-277	30K/35K/40K/50K	50000	WL,DIM,ES	5.7(w) 10.0(d)

Steel Body
Clear Lens
White Finish
80 / 90 CRI



Application



LED Recessed Remodel / New Construction Canless Downlight

Gimbal & Eyeball



Item#	Description	Watt	Lumen	CRI	Volt	Color Temp	Hours	Features	Dimension(in)
A	Gimbal								
82098-SU	LFX/GDL/3R/8W/5SCT	8	600	90	120	27K/30K/35K/40K/50K	50000	WL,DIM	1.8(w) 3.3(d)
B	Eyeball								
82083-SU	LFX/EDL/4R/12W/SCT	12	1000	80	120	27K/30K/35K/40K/50K	50000	WL,DIM,ES	1.7(w) 4.8(d)

Upgrade your indoor recessed can lighting with this energy efficient LED kit. These round retrofit lights are fully dimmable and simple for anyone to install with no electrician necessary. Medium base (E26) adapter screws directly into existing socket, connects to fixture, and the fixture slides directly into existing can. Gimbal design allows you to direct the light where you need it. They are ETL Listed for wet location installation

Aluminum Body
Clear Lens
White Finish
90 CRI



Application



LED Recessed Gimbal Downlight Retrofit Kits

Gimbal Head



2-Axis Gimbal
30° Tilt | 360° Rotation

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	82080-SU	8	700	120	27K/30K/35K/40K/50K	50000	WL,DIM,ES	2.6(w) 5.0(d)
B	82084-SU	11	1100	120	27K/30K/35K/40K/50K	50000	WL,DIM,ES	2.9(w) 7.2(d)

Retrofit your space with our LED retrofit downlight kit. Developed utilizing the latest in LED technology, with a lifetime of 50,000 hours, it is sure to stand the test of time, it gives your space a warm ambience with a homey feel. UL listed for damp locations and others are wet location certified, it can be installed indoors or outdoors and will stand against the elements.

Aluminum & Plastic Body
White Lens
White Finish
90 CRI

5
Year
Warranty



LED Recessed Downlight Retrofit Kits

Round & Square Trim



Baffle Smooth Color Selectable Switch

Round Trim



4" Round



5-6" Round

Item#	Description	Watt	Lumen	CRI	Volt	Color Temp	Hours	Features	Dimension(in)
4" Round									
87792-SU	LFX/RDL/4R/10W/SCT	10	700	90	120	27K/30K/35K/40K/50K	35000	WL,DIM,ES	1.9(w) 5.5(d)
4" Round Baffle									
87790-SU	LFX/RDL/BF/4R/10W/D/SCT	10	700	90	120	27K/30K/35K/40K/50K	35000	WL,DIM,ES	1.9(w) 5.5(d)
5-6" Round									
87793-SU	LFX/RDL/5/6R/14W/SCT	15	1100	90	120	27K/30K/35K/40K/50K	35000	WL,DIM,ES	1.9(w) 7.4(d)
5-6" Round Baffle									
87791-SU	LFX/RDL/BF/5/6R/14W/SCT	15	1100	90	120	27K/30K/35K/40K/50K	35000	WL,DIM,ES	1.9(w) 7.4(d)

Square Trim



4" Square



4" Square Slim



5-6" Square

Item#	Description	Watt	Lumen	CRI	Volt	Color Temp	Hours	Features	Dimension(in)
4" Square									
89200-SU	LFX/RDL/4S/11W/SCT	11	750	90	120	27K/30K/35K/40K/50K	50000	DL,DIM,ES	3.2(h) 5.0(w)
89278-SU	LFX/RDL/4S/10W/D/E/40K	10	700	80	120	4000K	50000	WL,DIM,ES	2.7(h) 4.9(w) 4.9(d)
4" Square Slim									
89124-SU	LFX/RDL/4S/9W/DIM/E/40K	9	630	80	120	4000K	50000	DL,DIM,ES	2.5(h) 5.0(w) 5.0(d)
5-6" Square									
89129-SU	LFX/RDL/5/6S/14W/SCT	14	1100	90	120	27K/30K/35K/40K/50K	50000	WL,DIM,ES	3.6 (h) 7.3(w) 7.3(d)

Specifications may change without notice.
 We are not responsible for any typographical errors



Metal Canopy
Decorative Glass Finish
81 CRI

5
Year Warranty

Application: Hospitality, Retail, Residential

LED Pendant Fixture

Glass Shade



The Sunlite Designers Glass LED Pendant collection features exquisite designs. Each pendant is meticulously crafted to provide high quality lighting. Every pendant features a unique stunning design that complements any room's interior. The pendants seamlessly integrate the latest and most efficient energy saving LED technology.



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A 88714-SU	LFX/DSG/PD/D/9W/JUNEAU	9	800	120	3000K	35000	DL,DIM	11.0(w) 4.8(d)
88715-SU	LFX/DSG/PD/9W/3SCT/JUN	9	600	120	30K/40K/50K	50000	DL,DIM	11.0(w) 4.8(d)
B 88710-SU	LFX/DSG/PD/D/9W/VENICE	9	800	120	3000K	35000	DL,DIM	9.0(w) 4.8(d)

Wood & Metal Body
White Lens
Brushed Nickel Finish
81 CRI

3
Year Warranty

Application: Hospitality, Retail, Residential

LED Pendant Fixture

Wood Shade



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
88672-SU	LFX/WC/PD/25W/S/SCT	25	1500	120	30K/40K/50K	50000	DL,DIM	7.0(w) 20.0(d)

Metal Body
 120 volts
 Medium (E26) Base
 Uses S19 Bulb(s)
 Bulb Not Included

Bulb Suggestion



Application



Pendant Fixture

Industrial Style

BULB
 REQUIRED



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
07078-SU	AQF/NC/PD/R	Black	-	3	60	11.0(h) 12.8(w) 32.5(d) 48 Cord

Metal Body
 120 volts
 Medium (E26) Base
 Uses S19 Bulb(s)
 Bulb Not Included

Bulb Suggestion



Application



Pendant Fixture

Antique Style

BULB
 REQUIRED



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
07082-SU	AQF/GPD/F/AB	Black	-	5	60	7.0(w) 26.5(d)

120 volts
Medium (E26) Base
Metal Body
ETL Listed
Bulbs Not Included

Bulb Suggestion



Pendant Fixture

Antique Style

**BULB
REQUIRED**

Application



A



B

Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A	07016-SU	AQF/PD/CN10/AB/FLA	Antique Brass	-	40	4.5(w) 10.5(d)
B	07009-SU	AQF/PD/SCN10/OB/AB	Antique Bronze	-	60	6.3(w) 10.0(d) 72 Cord



A



B



E



F



C



D




G

Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A	07060-SU	AQF/GPD/PR/AB	Antique Bronze	-	60	17.0(w) 15.0(d) 48 Cord
B	07010-SU	AQF/PD/HEX/AB	Antique Bronze	-	60	9.5(w) 6.9(d) 72 Cord
C	07011-SU	AQF/PD/CGC/IR	Iron Rust	-	60	10.6(w) 5.7(d) 42 Cord
D	07005-SU	AQF/PD/CN10/CG/OB	Oil Black	Clear Glass	60	11.5(w) 10.7(d) 68 Cord
E	07006-SU	AQF/PD/OCG/OB/CB	Vintage Oil Bronze	-	60	11.8(w) 6.5(d) 42 Cord
F	07003-SU	AQF/PD/CG/OB	Vintage Oil Bronze	-	40	8.3(w) 4.3(d) 72 Cord
G	07014-SU	AQF/PD/CG/WH	White	-	40	8.3(w) 4.3(d) 72 Cord

Pendant Fixture

Tinted Glass

BULB
REQUIRED



120 volts
Medium (E26) Base
Glass Body
UL Listed
Bulb Not Included

Bulb Suggestion



A19
Med E26

Application



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A 07020-SU	TG/PD/SP/9	Brushed Nickel	Tinted Glass	1	60	9.6(w) 8.3(d) 72 Cord
B 07022-SU	TG/PD/SP/6.5	Brushed Nickel	Tinted Glass	1	60	7.0(w) 6.9(d) 72 Cord
C 07024-SU	TG/PD/SP/7	Brushed Nickel	Tinted Glass	1	60	7.6(w) 5.5(d) 72 Cord

Clear Glass



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A 07074-SU	AQF/CG/PD/VCYL	Black	Clear Glass	1	60	11.6(w) 7.0(d) 50 Cord
B 07002-SU	AQF/PD/CN/CB/CAC	Copper Bronze	Clear Acrylic	1	60	9.4(w) 5.7(d) 71 Cord
C 07046-SU	AQF/CG/PD/TCYL	Black	Clear Glass	1	60	12.0(w) 9.6(d) 49 Cord



120 volts
Medium (E26) Base
Metal Body
Bulb Not Included

Bulb Suggestion



A19
Med E26



T10
Med E26

Application



Hospitality



Office



Retail



Commercial



Residential

Pendant Fixture

Decorative

**BULB
REQUIRED**



A




B

Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)	
A	07094-SU	AQF/GPD/DS/MB	Matt Black	-	1	60	22.0(h) 20.4(w) 20.4(d) 51 Cord
B	07084-SU	AQF/4TPD/AB	Antique Black	-	4	60	34.5(h) 8.0(w) 8.0(d) 65 Cord

120 volts
Candelabra (E12) Base
Metal Body
Bulb Not Included

Bulb Suggestion



Candelabra
E12

Application



Hospitality



Retail



Commercial



Residential

Pendant Fixture

5 Branch white textured Chandelier

**BULB
REQUIRED**



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
04447-SU	CH5WT	Textured White	-	5	60	16.0(h) 16.75(w) 16.75(d)

120 volts
Medium (E26) Base
Metal Body
ETL Listed
Bulb Not Included

Bulb Suggestion



Pendant Fixture

Globe Style

**BULB
REQUIRED**

Application



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A 46058-SU	FIX/PRS/E26/BK	Matte Black	-	1	60	52 (h) 8 (d)
B 46057-SU	FIX/PRS/E26/BN	Brushed Nickel	-	1	60	52 (h) 8 (d)

120 volts
Medium (E26) Base
Metal Body
UL Listed
Bulb Not Included

Bulb Suggestion



Pendant Fixture

Black and Copper

**BULB
REQUIRED**


Application



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A 07026-SU	PD/IC/14	Matte Black	-	1	60	8.5(w) 14.3(d) 78 Cord
B 07028-SU	PD/IC/7	Matte Black	-	1	60	16.0(w) 7.3(d) 74 Cord




120 volts
Max 60 Watts
Medium (E26) Base
Metal Body
UL Listed-Dry Location
Bulb Not Included

Bulb Suggestion



A19
Med E26

Application






Hospitality Retail Residential


Pendant Fixture

Colored Canopy

**BULB
REQUIRED**



Blue




Baby Blue

Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
88752-SU	CF/PD/Z/B	Blue	-	1	60	10.0(w) 10.0(d) 48 Cord
88754-SU	CF/PD/Z/BB	Baby Blue	-	1	60	10.0(w) 10.0(d) 48 Cord
88755-SU	CF/PD/Z/M	Mint	-	1	60	10.0(w) 10.0(d) 48 Cord
88744-SU	CF/PD/V/BB	Baby Blue	-	1	60	5.3(w) 12.0(d) 48 Cord




120 volts
Medium (E26) Base
Plastic Body
Only Lamp holder
42" Cord

Bulb Suggestion



A19
Med E26


Application

Hospitality Retail Residential

Colored Canopy

Nova



A

B



Blue UFO Pendant
Fixture Light Bulbs



Pink UFO Pendant
Fixture Light Bulbs


Item#	Description	Lumen	MOL(in)
80762-SU	UFO/LED/7W/30K/BLUE	550	2.6
80764-SU	UFO/LED/11W/30K/BLUE	800	2.6
80766-SU	UFO/LED/15W/30K/BLUE	1250	3

Item#	Description	Lumen	MOL(in)
80763-SU	UFO/LED/7W/30K/PINK	550	2.6
80765-SU	UFO/LED/11W/30K/PINK	800	2.6
80767-SU	UFO/LED/15W/30K/PINK	1250	3

Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A 80758-SU	CO/PD/BL	Blue	-	1	40	4.0(w) 1.8(d)
B 80759-SU	CO/PD/PK	Pink	-	1	40	4.0(w) 1.8(d)






120 volts
Medium (E26) Base
Metal Body
UL Listed
Bulb Not Included

Bulb Suggestion



A19
Med E26

Application

Hospitality Office Retail Commercial Residential

Pendant Fixture

Socket


BULB
REQUIRED



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A	07034-SU AQF/BS/S1/T	Antique Bronze	-	1	40	3.5(w) 1.8(d) 42 Cord
B	07095-SU AQF/PD/BR	Brown	-	1	60	4.2(w) 1.8(d) 72 Cord
C	07001-SU AQF/PD/S3/CB	Copper Bronze	-	3	60	5.3(w) 6.0(d) 42 Cord






Surface Mount
120 volts
Medium (E26) Base
Metal Body
UL Listed
Bulb Not Included

Bulb Suggestion



A19
Med E26

Application

Hospitality Office Retail Commercial Residential

Ceiling Semi Flush Mount

Socket

BULB
REQUIRED



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A	46071-SU FIX/LH/E26/BK/5"	Black	-	1	60	2.8(h) 5.0(d)
B	90163-SU FIX/1LT/PB/E26	Polished Brass	-	1	60	3.0(h) 6.0(d)

Specifications may change without notice.
 We are not responsible for any typographical errors

Sunlite's LED ceiling fixtures are designed for years of maintenance-free service. The brushed nickel finish highlights the stylish and clean appearance that will complement any decor. These dimmable fixtures have energy-efficient LED technology built-in, they are also ETL Listed for damp location installation with a life span of up to 50,000 hours. Ideal for offices, hotel rooms, bedrooms, bathrooms, kitchens, dining areas, entryways, or anywhere downlights are needed.

LED Ceiling Flush Mount

Double Band Trim



Adjust the color temperature of your room's lighting design!

27K 30K 35K 40K 50K

Steel & Acrylic Body
White Lens
90 / 80 CRI

Options



Application



Oil Rubbed Bronze Finish



Polish Brass Finish

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
10" 12" 14" 16" 18" Diameter Brushed Nickel Finish								
88489-SU	LFX/DCO/10"/15W/90CRI/5SCT/BN	15	1000	120	27K/30K/35K/40K/50K	50000	DL,DIM	3.0(h) 10.0(d)
87812-SU	LFX/DCO/12"/15W/90CRI/5SCT/BN/V2	15	1120	120	27K/30K/35K/40K/50K	50000	DL,DIM,ES,T20	2.87(h) 12.0(d)
87813-SU	LFX/DCO/14"/21W/90CRI/5SCT/BN/V2	21	1500	120	27K/30K/35K/40K/50K	50000	DL,DIM,ES	2.87(h) 14.0(d)
87775-SU	LFX/DCO/14"/21W/SCT/BN/MV	21	1500	100-277	30K/40K/50K	50000	DL,DIM	3.5(h) 14.0(d)
87796-SU	LFX/DCO/16"/24W/90CRI/5SCT/BN	24	1700	120	27K/30K/35K/40K/50K	50000	DL,DIM,ES	2.87(h) 16.0(d)
87776-SU	LFX/DCO/16"/24W/SCT/BN/MV	24	1700	120-277	30K/40K/50K	50000	DL,DIM	4.0(h) 16.0(d)
87797-SU	LFX/DCO/18"/28W/90CRI/5SCT/BN	28	1960	120	27K/30K/35K/40K/50K	50000	DL,DIM,ES	4.0(h) 18.0(d)
87777-SU	LFX/DCO/18"/28W/SCT/BN/MV	28	2000	100-277	30K/40K/50K	50000	DL,DIM	4.0(h) 18.0(d)
12" 14" 16" Diameter Oil Rubbed Bronze Finish								
49052-SU	LFX/DCO/12"/17W/SCT/ORB	17	1050	120	27K/30K/35K/40K/50K	50000	DL,DIM,ES	3.3(h) 12.0(d)
49062-SU	LFX/DCO/14"/20W/SCT/ORB	20	2000	120	27K/30K/40K/50K/65K	50000	DL,DIM	2.9(w) 14.0(d)
49160-SU	LFX/DCO/16"/25W/SCT/ORB	25	2500	120	27K/30K/40K/50K/65K	50000	DL,DIM	4.0(h) 16.0(d)
12" 14" 16" Diameter Polish Brass Finish								
50436-SU	LFX/DCO/14"/20W/SCT/PB	20	2000	120	27K/30K/40K/50K/65K	50000	DL,DIM	2.9(h) 14.0(d)

Sunlite's LED decorative band trim fixtures feature a stylish design with a clean appearance. It's decorative brushed nickel band trim adds a touch of elegance to any room's decor. It provides general illumination and is ideal for bedrooms, hotels, offices and many other settings.

Steel & Acrylic Body
White Lens
Brushed Nickel Finish
Emergency Battery Backup
80 CRI

Options



Application



LED Ceiling Flush Mount

Emergency Backup & Motion Sensor



A



Emergency Battery Back up



B

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	12", 14" Diameter Without Battery Backup							
88696-SU	LFX/DC0/12"/15W/SCT/BN/DEEP	15	1050	120	30K/40K/50K	50000	DL,DIM,ES	4.5(h) 12.0(d)
88689-SU	LFX/DC0/14"/BN/21W/ 90CRI/SCT/DEEP	21	1500	120	30K/40K/50K	50000	DL,DIM	4.0(h) 14.0(d)
B	12" Diameter Emergency Battery Backup							
45601-SU	LFX/DC012/BN/15W/D/40K/EM	15	1100	120	4000K	50000	DL,DIM	4.5(w) 12.0(d)
87779-SU	LFX/DC012/BN/15W/SCT/MV/EM	15	1050	100-277	30K/40K/50K	50000	DL,DIM	4.5(w) 12.0(d)
87781-SU	LFX/DC016/BN/24W/SCT/MV/EM	24	1700	100-277	30K/40K/50K	50000	DL,DIM	4.5(w) 16.0(d)
	14" Diameter Emergency Battery Backup							
87780-SU	LFX/DC014/BN/21W/SCT/MV/EM	21	1500	100-277	30K/40K/50K	50000	DL,DIM	4.5(w) 14.0(d)
	16" Diameter Emergency Battery Backup							
50139-SU	LFX/DBN16/20W/BN/5SCT	20	2000	120	27K/30K/40K/50K/65K	50000		4.5(w) 16.0(d)
	18" Diameter Emergency Battery Backup							
87782-SU	LFX/DC018/BN/28W/SCT/MV/EM	28	2000	100-277	30K/40K/50K	50000	DL,DIM	4.5(w) 18.0(d)



Steel & Acrylic Body
White Lens
Brushed Nickel Finish
81 CRI

Options



Application



LED Ceiling Flush Mount

Double Band Oval Trim



A Brushed Nickel



B Black

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	Brushed Nickel Finish							
49176-SU	LFX/DC032/OVAL/BN/35W/SCT	35	3000	100-277	30K/40K/50K	50000	DL,DIM,ES	4.5(h) 18.0(w) 32.5(d)
B	Black Finish							
49175-SU	LFX/DC032/OVAL/BLK/35W/SCT	35	3000	100-277	30K/40K/50K	50000	DL,DIM,ES	4.5(h) 18.0(w) 32.5(d)

Specifications may change without notice. We are not responsible for any typographical errors

LED Ceiling Semi Flush Mount

Double Band Trim

These easy to install, dimmable fixtures have energy-efficient LED technology built-in, so there are no bulbs to replace. The output is a bright, flicker-free 1050 lumen. These selectable fixtures feature innovative technology that allows you to choose the color temperature at the time of installation. Select 3000K Warm White, 4000K Cool White, or 5000K Super White depending on your preference using a switch located on the back. Energy Star Certified and may qualify for state and local rebates.



A Brushed Nickel

B Oil Rubbed Bronze

Steel & Acrylic Body
White Lens
Brushed Nickel / Oil Rubbed Bronze Finish
80 CRI

Options

5 Year Warranty

Motion Sensor

Application

Commercial Residential

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A 87783-SU	LFX/DC012/P/BN/15W/SCT	15	1050	120	30K/40K/50K	50000	DL,DIM	9.0(w) 12.0(d)
B 87784-SU	LFX/DC012/P/ORB/15W/SCT	15	1050	120	30K/40K/50K	50000	DL,DIM	9.0(w) 12.0(d)

LED Ceiling Semi Flush Mount

Solid Band Trim

Sunlite LED 15-inch semi flush mount ceiling fixtures are designed for years of maintenance-free service. The brushed nickel finish highlights the stylish and clean appearance that will complement any decor. These easy to install, dimmable fixtures have energy efficient LED technology built-in so there are no bulbs to replace. Ideal for offices, hotel rooms, bedrooms, bathrooms, kitchens, dining areas, entryways or anywhere downlights are needed. They are also UL Listed for damp location installation. With a life span of up to 50,000 hours they are an ideal, no maintenance solution for both residential and commercial installations. ETL Listed for damp location installation.



Steel & Acrylic Body
Acrylic Lens
Brushed Nickel / Oil Rubbed Bronze Finish
80 CRI

5 Year Warranty

Application

Hospitality Office Retail Commercial Residential

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
81305-SU	LFX/MPM/15"/30W/SCT/SN	30	1950	120	30K/40K/50K	50000	DL,DIM	9.0(w) 15.0(d)

Steel & Glass Body
Frosted Lens
Brushed Nickel Finish
81 CRI

Options

5 Year Warranty | Battery Backup | Motion Sensor

Application

Hospitality | Commercial | Residential

LED Ceiling Flush Mount

Half Band & Half Glass Trim



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
49154-SU	LFX/R/GL/20W/5SCT/BN	20	1000	120	27K/30K/35K/40K/50K	50000	DL,DIM	2.5(w) 11.0(d)

Steel & Acrylic Body
White Lens
Brushed Nickel Finish
80 CRI

Options

5 Year Warranty | Photocell | Motion Sensor

Application

Commercial | Residential

LED Ceiling Flush Mount

Double Band Trim With Extended Lens



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
13" Diameter								
82001-SU	LFX/DFM/13"/20W/BN/SCT	20	1400	100-277	30K/40K/50K	50000	DL,DIM	4.0(w) 13.0(d)
18" Diameter								
87786-SU	LFX/DFM/18"/25W/BN/SCT	25	1500	120	30K/40K/50K	50000	DL,DIM	4.0(w) 17.0(d)

Steel Body
Frosted Glass Lens
Brushed Nickel Finish
80 CRI

5 Year Warranty

Application

Commercial | Residential

LED Ceiling Flush Mount

Dome Style



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
49064-SU	LFX/DBN13/EL/FR/20W/MV/30K	20	100-277	1400	3000K	50000	DL,DIM	5.25(w) 13.35(d)
81036-SU	LFX/DBN13/EL/FR/20W/MV/40K	20	100-277	1400	4000K	50000	DL,DIM	5.25(w) 13.35(d)
49055-SU	LFX/DBN15/EL/FR/23W/120V/30K	23	120	1380	3000K	50000	DL,DIM	7.5(w) 15.0(d)



Steel & Plastic Body
 White Lens
 Brushed Nickel & Fabric Finish
 81 CRI

3
 Year
 Warranty

Application

 Hospitality
  Retail
  Residential

LED Ceiling Flush Mount

Fabric Shade Drum Style








Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
49161-SU	LFX/FD/13"/20W/3SCT/BN	20	1100	120	30K/40K/50K	35000	DL,DIM	5.0(w) 13.0(d)
49086-SU	LFX/FD/17.5/28W/DIM/BN/SCT	28	1680	120	27K/30K/35K/40K/50K	35000	DL,DIM	5.0(w) 17.0(d)

Aluminum Body
 White Lens
 PMMA Optical Lens
 White Finish
 80 CRI

5
 Year
 Warranty

Application

 Education
  Medical
  Office
  Industrial
  Retail
  Commercial
  Residential

LED Ceiling Flush Mount

Flat Panel



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
87746-SU	LFX/1X1/10W/SCT	10	920	120	30K/35K/40K/45K/50K	50000	DL,DIM	1.1(h) 11.9(w) 11.9 (d)



Steel Body
Frosted Lens
Black Finish
80 CRI

5
Year
Warranty

Application



LED Ceiling Flush Mount

Decorative Band Trim



A



B

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	81042-SU LFX/DDS/13"/20W/SCT/BK/GD	20	1000	120	30K/40K/50K	50000	DL,DIM	4.0(h)13.0(w) 13.0(d)
B	81045-SU LFX/DDR/13"/20W/SCT/BK/GD	20	1000	120	30K/40K/50K	50000	DL,DIM	4.0(h)13.0(d)

Steel Body
White Lens
Black Finish
80 CRI

3
Year
Warranty

Application



LED Ceiling Flush Mount

Drum Style



A



B

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	81377-SU LFX/DCF/15W/30K/11"/BK	15	950	120	30K/40K/50K	25000	DL	4.0(h) 11.0(d)
B	50740-SU LFX/RND/15W/3SCT/5"/BK	15	1000	120	30K/40K/50K	50000	DL, DIM	2.0(h) 4.75(d)



Aluminum & Steel Body
 Frosted Glass Lens
 Black Finish
 80 CRI

5
 Year
 Warranty

Application



LED Ceiling Flush Mount

Pyramid Design



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
81328-SU	LFX/PYR/12W/3SCT/BK	12	650	120	30K/40K/50K	5000	DL	5.0(h) 10.3(w) 10.3(d)

Steel & Glass Body
 White Lens
 Black Finish
 81 CRI

5
 Year
 Warranty

Application



LED Ceiling Flush Mount

Decorative Band Trim



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
87769-SU	LFX/DCO/13"/20W/SCT/BK	20	1050	120	30K/40K/50K	50000	DL,DIM	3.0(w) 13.0(d)

Steel & Acrylic Body
white Lens
White Finish
80 CRI

5 Year Warranty

Application

Commercial Residential

LED Ceiling Flush Mount

Mushroom Solid Band Trim



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
87765-SU	LFX/AM/11"/15W/SCT	15	1050	100	27K/30K/35K/40K/50K	50000	DL,DIM,ES	3.3(w) 10.0(d)
87766-SU	LFX/AM/13"/21W/SCT	21	1450	100	27K/30K/35K/40K/50K	50000	DL,DIM,ES	3.6(w) 13.0(d)

Plastic Body
Clear Lens
White Finish
80 CRI

5 Year Warranty

Application

Commercial Residential

LED Ceiling Flush Mount

Solid Band Trim



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
87767-SU	LFX/SCF/10"/15W/SCT	15	1050	120	27K/30K/35K/40K/50K	50000	DL,DIM,ES	2.2(w) 10.0(d)
87768-SU	LFX/SCF/13"/21W/SCT	21	1450	120	27K/30K/35K/40K/50K	50000	DL,DIM,ES	2.2(w) 13.0(d)

Plastic Body
Clear Lens
White Finish
80 CRI

5 Year Warranty

Application

Commercial Residential

LED Ceiling Flush Mount

Square Mushroom Style



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
88690-SU	LFX/MU/SQ/11"/16W/E/D/30K	16	1200	120	3000K	50000	DL,DIM	3.0(h) 11.0(w) 11.0(d)
88691-SU	LFX/MU/SQ/11"/16W/E/D/40K	16	1200	120	4000K	50000	DL,DIM	3.0(h) 11.0(w) 11.0(d)
88692-SU	LFX/MU/SQ/14"/24W/E/D/30K	24	1750	120	3000K	50000	DL,DIM	2.8(h) 15.0(w) 15.0(d)
88693-SU	LFX/MU/SQ/14"/24W/E/D/40K	24	1750	120	4000K	50000	DL,DIM	2.8(h) 15.0(w) 15.0(d)

Sunlite's LED 11-inch round ceiling fixtures are designed for years of maintenance-free service. The simplistic white mushroom design blends in with any room. These easy to install, dimmable fixtures have energy-efficient LED technology built-in, so there are no bulbs to replace. Ideal for bedrooms, bathrooms, kitchens, hallways, closets, entryways, or anywhere downlights are needed. They are also ETL Listed for safety with a life span of up to 50,000 hours.

LED Ceiling Flush Mount

Round Mushroom Style



Plastic Body
Clear Lens
White Finish
80 CRI



Application



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
87762-SU	LFX/MU/11"/16W/SCT	16	1200	120	27K/30K/35K/40K/50K	50000	DL,DIM,ES	3.7(h) 11.0(d)
87763-SU	LFX/MU/11"/20W/SCT	20	1500	120	27K/30K/35K/40K/50K	50000	DL,DIM,ES	3.7(h) 11.0(d)
87764-SU	LFX/MU/14"/24W/SCT	24	1800	120	27K/30K/35K/40K/50K	50000	DL,DIM,ES	4.6(h) 14.0(d)
87749-SU	LFX/MU/15"/25W/SCT5	25	1750	120	27K/30K/35K/40K/50K	50000	DL,DIM,ES	4.6(h) 15.16(d)
49120-SU	LFX/MU/19"/MW/SCT	24/28/32	1680/1960/2240	120	27K/30K/35K/40K/50K	50000	DL,DIM,ES	4.1(w) 19.0(d)

Before Installation

After Installation



Metal & Acrylic Body
White Lens
White Finish
80 CRI



Application



LED Ceiling Flush Mount

Pull Chain Socket



Remove the existing light bulb in the old socket and screw the new fixture right into the old socket. No electrician needed.

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
88670-SU	LFX/E26/7"/10W/30K	10	700	100-277	3000K	50000	DL	5.0(w) 7.5(d)
88671-SU	LFX/E26/7"/10W/40K	10	700	100-277	4000K	50000	DL	5.0(w) 7.5(d)


Energy efficient Sunlite LED ceiling fixtures are designed for years of maintenance-free service. These surface mount mini downlights have a slim and simplistic design with brushed nickel trim that fits perfectly into any modern setting. These easy to install, dimmable fixtures have energy efficient LED technology built-in so there are no bulbs to replace. Ideal for closets, hallways, stairways, entryways, storage areas, basements, or anywhere downlight is needed. They are also ETL Listed for damp location installation. With a life span of up to 50,000 hours they are an ideal, no maintenance solution for both residential and commercial installations.

Aluminum & Acrylic Body
White Lens
Bronze / White Finish
90 CRI



LED Ceiling Flush Mount

Premium Design



7" Emergency Battery

81269-SU Emergency Battery

Trim

50206-SU TRIM/MP/5R/BLACK

50208-SU TRIM/MP/7R/BLACK



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	Round 5",7",9",12"							
81282-SU	LFX/MP/5R/10W/E/D/SCT/WH	10	600	120	30K/40K/50K	50000	DL,DIM	0.6(w) 5.5(d)
81284-SU	LFX/MP/7R/15W/E/D/SCT/WH	15	900	120	30K/40K/50K	50000	DL,DIM	0.6(w) 7.4(d)
81286-SU	LFX/MP/9R/18W/E/D/SCT/WH	18	1100	120	30K/40K/50K	50000	DL,DIM	0.6(w) 9.0(d)
81289-SU	LFX/MP/12R/22W/CRI90/5SCT/WH	22	1450	120	27K/30K/35K/40K/50K	50000	DL,DIM	0.5(w) 11.75(d)
B	Square 5",9"							
81283-SU	LFX/MP/5S/10W/E/D/SCT/WH	10	600	120	30K/40K/50K	50000	DL,DIM	0.6(h) 4.4(d)
81287-SU	LFX/MP/9S/18W/E/D/SCT/WH	18	1100	120	30K/40K/50K	50000	DL,DIM	0.6(h) 9.0(w) 9.0(d)

Sunlite's color selectable mini panel fixture with motion sensor, allows for selecting the light temperature to match a wide range of applications while saving even more energy by illuminating only when needed. The color selectable switch placed on the fixture's side, allows the user to choose between five white color temperatures, ranging from 2700K to 5000K. The Infrared motion sensor located on the fixture, helps save even more energy by either dimming the light output (bi-level) or turning off (on/off) when no motion is detected. This feature can be disabled by simply switching to "off."

Plastic Body
White Lens
White Finish
Built-in Bi-Level Motion Sensor
90 CRI



LED Ceiling Flush Mount

Motion Closet Light



On/Off / Bi-Level Sensor



SCT Switch

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
81325-SU	LFX/MP/5R/12W/MS/SCT	12	700	120	27K/30K/35K/40K/50K	50000	DL,DIM,ES	0.9(w) 5.7(d)
81327-SU	LFX/MP/8R/13W/MS/SCT	13	1000	120	27K/30K/35K/40K/50K	50000	DL,DIM,ES	0.9(w) 8.2(d)
81329-SU	LFX/MP/12R/18W/MS/SCT	18	1400	120	27K/30K/35K/40K/50K	50000	DL,DIM,ES	0.9(w) 12.1(d)

Sunlite LED disc ceiling fixtures are designed for years of maintenance-free service. The bronze metallic finish highlights the stylish and clean appearance that will complement any decor. These easy to install fixtures have energy efficient LED technology built-in so there are no bulbs to replace. Ideal for offices, bedrooms, bathrooms, hotel rooms, hallways, entryways or anywhere downlight is needed. They are also UL Listed for use in damp locations. Installing these Energy Star Certified fixtures may qualify you for state and local energy rebates. With a life span of up to 50,000 hours they are an ideal, no maintenance solution for both residential and commercial use.

Metal Body
White Lens
Bronze or White Finish
90 CRI

5
 Year
 Warranty

Application



LED Ceiling Flush Mount

Slim Disc Light



Recessed
 Housing Retrofit



E26 Retrofit Kit and Recessed
 Housing Included

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
White Finish Recessed Housing Retrofit & Junction box Installation								
87798-SU	LFX/DISC/6"/10W/5SCT	10	650	120	27K/30K/35K/40K/50K	50000	WL,DIM	1.29(h) 5.47(d)
87799-SU	LFX/DISC/7"/15W/5SCT/V2	15	950	120	27K/30K/35K/40K/50K	50000	WL,DIM	1.34(h) 7.28(d)

Metal & Acrylic Body
White Lens
Brushed Nickel / Oil Rubbed Bronze Finish
81 CRI

5
 Year
 Warranty

Application



LED Ceiling Flush

Solid Band Slim Design



A



B

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A Brushed Nickel Finish								
88312-SU	LFX/DC07/MINI/15W/90CRI/5SCT/BN	15	950	120	27K/30K/35K/40K/50K	50000	DL,DIM	1.3(w) 7.4(d)
B Oil Rubbed Bronze Finish								
88698-SU	LFX/DC07/MINI/ORB/15W/SCT	15	1000	120	30K/40K/50K	50000	WL,DIM	1.3(w) 7.4(d)



Metal & Glass Body
Clear Lens
Black / White Finish
80 CRI

2
Year
Warranty

Application

Education Hospitality Office Commercial Residential

Decorative Ceiling Flush Mount

Floating Transitional Glass



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A Black Finish								
88678-SU	LFX/FGF/17W/40K/8"/BK/2PK	17	1200	120	4000K	15000	DL,DIM	2.0(w) 8.0(d)
B White Finish								
88675-SU	LFX/FGF/17W/30K/8"/WH/2PK	17	1200	120	3000K	15000	DL,DIM	2.0(w) 8.0(d)
88676-SU	LFX/FGF/17W/40K/8"/WH/2PK	17	1200	120	4000K	15000	DL,DIM	2.0(w) 8.0(d)

Sunlite's LED decorative fixtures feature a stylish design with a clean appearance. It's decorative brushed nickel band trim adds a touch of elegance to any room's decor. It provides general illumination and is ideal for bedrooms, hotels, offices and many other settings.

Metal & Glass Body
Alabaster Lens
Brushed Nickel Finish
90 CRI

5
Year
Warranty

Application

Commercial Residential

LED Ceiling Flush Mount

Alabaster Glass Lens



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A 12" Diameter								
50157-SU	LFX/DBN12/17W/BN/SCT	17	1500	120	27K/30K/35K/40K/50K	25000	DL,DIM	4.8(w) 12.0(d)
B 13" 15" Diameter								
87785-SU	LFX/DBN13/20W/BN/AL/SCT	20	1200	120	30K/40K/50K	50000	DL,DIM	4.8(w) 13.0(d)
87778-SU	LFX/DBN15/25W/BN/AL/SCT	25	1610	120	30K/40K/50K	50000	DL,DIM	4.8(w) 15.0(d)

120 volts
Med (E26) /GU24 Base
Uses A19 Bulb(s)
Metal & Glass Body
UL Listed

Bulb Suggestion



Ceiling Flush Mount

Glass Lens

**BULB
REQUIRED**

Application



A



B



C



D



E



F

Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A	Alabaster Lens					
46000-SU	S1000A	Weathered Bronze	Alabaster Glass	3	60	7.9(w) 15.4(d)
B	Distressed Brown-Alabaster Lens Med (E26)					
46075-SU	DDB13/AL	Distressed Brown	Alabaster Glass	2	60	5.8(w) 13.3(d)
46078-SU	DDB15/AL	Distressed Brown	Alabaster Glass	3	60	5.5(w) 15.3(d)
C	Polished Brass-White Lens Med (E26)					
04574-SU	DBS11/FR	Polished Brass	Frosted Glass	2	60	6.0(w) 11.0(d)
04582-SU	DBS13/FR	Polished Brass	Frosted Glass	2	60	6.0(w) 13.3(d)
D	Polished Brass-Clear Lens Med (E26)					
04572-SU	DBS11/CL	Polished Brass	Clear Glass	2	60	5.3(w) 11.3(d)
04580-SU	DBS13/CL	Polished Brass	Clear Glass	2	60	6.3(w) 13.0(d)
E	Brushed Nickel-Alabaster Lens Med (E26)					
04587-SU	DBN11/AL	Brushed Nickel	Alabaster Glass	2	60	11.3(w) 11.3(d)
04588-SU	DBN13/AL	Brushed Nickel	Alabaster Glass	2	60	5.3(w) 13.3(d)
F	Smooth White-White Lens Med (E26)					
04578-SU	DWS11/FR	Smooth White	Frosted Glass	2	60	5.3(w) 11.5(d)
04586-SU	DWS13/FR	Smooth White	Frosted Glass	2	60	6.3(w) 13.0(d)

120 volts
GU24 Base
Uses CFL / LED Bulb(s)
Metal & Glass Body
UL Listed

Bulb Suggestion



Ceiling Flush Mount

Ceiling Fixtures

**BULB
REQUIRED**



Application



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
45576-SU	DCO14/E/PB	Polished Brass	White Acrylic	2	23	3.5(w) 14.0(d)



120 volts
Med (E26) /GU24 Base
Uses CFL / LED Bulb(s)
Metal & Glass Body
UL Listed

Bulb Suggestion

A19 Med E26 A19 GU 24

Application

Commercial Residential

Ceiling Flush Mount

Ceiling Fixtures

**BULB
REQUIRED**



A



B



C



D



E



F



G




H

Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A	04540-SU 112/PC/WH	Floral Frosted White Glass	White Glass	2	60	5.2(h) 11.4(w) 11.4(d)
B	04425-SU KIT6/CH	Chrome	Clear/White Glass	1	60	4.3(w) 6.8(d)
C	04498-SU HALL8/PB/GU24/2-18	Polished Brass	White Glass	2	60	4.8(w) 8.8(d)
D	04490-SU HALL6/WH	White	White Glass	1	60	5.0(w) 6.0(d)
E	04455-SU GLO6/WH	White	White Glass	1	60	7.0(w) 6.0(d)
F	04476-SU GLO8/BN	Brushed Nickel	Alabaster Glass	1	100	9.0(w) 8.0(d)
G	04477-SU GLO8/PB/GU24/1-18	Polished Brass	White Glass	1	100	9.0(w) 8.0(d)
H	04501-SU PINE3/4/GU24/1-18	Polished Brass	Clear Textured	1	60	6.8(w) 5.4(d)


120 volts
4-Pin Base
Uses FC8T9 Bulb
UL Listed

Bulb Suggestion



T9 Circline

Application

Commercial Residential

Ceiling Flush Mount

Fluorescent Circline Style

**BULB
REQUIRED**



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
Chrome						
04375-SU	22/CR	Chrome	-	1	22	3.5(w) 8.5(d)
04390-SU	32/CR	Chrome	-	1	32	3.5(w) 12.3(d)
04405-SU	54/CR	Chrome	-	1	32	3.5(w) 12.3(d)

Metal Body
Clear Lens
Chrome Finish
80 CRI

3
Year
Warranty

Application



LED Adjustable Track Light

4 Lights



Arms can be rotate 330°





Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
81146-SU	LFX/TRL/4H/23W/30K/CH	23	1200	120	3000K	50000	DL,DIM	7.0(h) 4.8(w) 32.0(d)



Adjustable Track Light

3 Lights / 5 Lights / 6 lights



A



B



C

Surface Mount
120 volts
GU10 Base
Metal Body
ETL Listed
Bulb Not Included

Bulb Suggestion




MR16
GU10

Application



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A 45065-SU	FIX/TRL/3H/24"/BN	Brushed Nickel	-	3		5.5(h) 24.0(w) 5.0(d)
B 45063-SU	FIX/TRL/5H/45"/BN	Brushed Nickel	-	5		5.5(h) 45.0(w) 5.0(d)
C 45064-SU	FIX/TRL/6H/54"/BN	Brushed Nickel	-	6		5.5(h) 54.0(w) 5.0(d)



Aluminum & Plastic Body
White Lens
Brushed Nickel Finish
80 CRI

5 Year Warranty

Application: Hospitality, Commercial, Residential

LED Wall Mount Sconce

Decorative Wall Sconce



A



B



C



D

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	85098-SU LFX/WS/12W/SCT/BN	12	800	120	30K/40K/50K	50000	DL,DIM	10.0(h) 5.0(w)
B	85099-SU LFX/WS/12W/SCT/BN	12	800	120	30K/40K/50K	50000	DL,DIM	10.0(h) 5.0(w)
C	85100-SU LFX/WS/12W/SCT/BN	12	800	120	30K/40K/50K	50000	DL,DIM	10.0(h) 5.0(w)
D	85101-SU LFX/WS/12W/SCT/BN	12	800	120	30K/40K/50K	50000	DL,DIM	10.0(h) 5.0(w)

Steel & Plastic Body
White Acrylic Lens
Brushed Nickel Finish
80 CRI

5 Year Warranty

Application: Hospitality, Retail, Commercial, Residential

LED Wall Mount Sconce

Decorative Wall Sconce



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
81034-SU	LFX/WS/15W/30K/BN	15	850	120	3000K	50000	DL,DIM	13.5(h) 4.5(w) 4.0(d)



Metal & Plastic Body
 White Lens
 Brushed Nickel / Bronze Finish
 81 CRI

5
 Year
 Warranty

Application

 Hospitality
  Commercial
  Residential

LED Wall Mount Sconce

Half Cylinder

LED
 BUILT-IN

SWITCH
 Color Selectable

SWITCH
 Power Selectable

90
 CRI



A



B



C




D

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	49200-SU LFX/HC/MW/3SCT/BN	11/15/23	850/1150/1650	120	30K/40K/50K	50000	DL,DIM	10.5(h) 8.0(w) 3.7(d)
B	82023-SU LFX/HC/ORB/15W/SCT	15	950	120	30K/40K/50K	50000	WL,DIM,ES	10.0(h) 7.0(w) 3.0(d)
C	82002-SU LFX/DHC/ORB/12W/SCT	12	840	100-277	30K/40K/50K	50000	DL,DIM	13.0(h) 8.0(w) 4.0(d)
D	88679-SU LFX/WS/CHC/15W/SCT/BN	15	1050	120	30K/40K/50K	50000	DL,DIM	10.0(h) 5.0(w)

Aluminum & Plastic Body
 White Lens
 Brushed Nickel Finish
 90 / 81 CRI

5
 Year
 Warranty

Application

 Hospitality
  Retail
  Commercial
  Residential

LED Wall Mount Sconce


Half Moon Wall Sconce

LED
 BUILT-IN

SWITCH
 Color Selectable



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
49201-SU	LFX/HM/12W/CRI90/3SCT/BN	12	840	120	30K/40K/50K	50000	DL,DIM	6.5(h) 12.0(w) 3.85(d)



Metal Body
Seeded clear glass
Brushed Nickel Finish
80 CRI

5
Year
Warranty

Application

 Hospitality
  Commercial
  Residential

LED Wall Mount Sconce

Clear Seedy Glass






Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
81033-SU	LFX/WS/SEEDY/2LT/15W/30K/BN	15	1000	120	3000K	50000	DL,DIM	12.0(h) 5.0(w) 4.0(d)

This Sunlite LED 6-watt brushed nickel indoor wall sconce light fixture has a classic design with modern LED technology built-in. With a long 50,000 hour lifespan this dimmable fixture will provide years of maintenance free service. Ideal for bedside, bathrooms, powder rooms, and more. It can be mounted with the white acrylic shade pointing up or down. Built in on/off switch on the base for manual control. Light output is a bright 420 lumens at 3000K warm white color temperature. Equivalent to a 25 watt light bulb while only using 6 watts of electricity.

Aluminum & Steel Body
White Lens
Brushed Nickel Finish
80 CRI

5
Year
Warranty

Application

 Hospitality
  Commercial
  Residential

LED Wall Mount Fixture

1 Light Sconce with Switch



On / Off Switch

Item#	Description	Watt	Lumen	Volt	Color TempW	Hours	Features	Dimension(in)
88685-SU	LFX/WS/30K/6W/LT/BN/8"	6	420	120	3000K	50000	DL,DIM,ES	8.0(h) 4.5(w) 3.8(d)

These Sunlite decorative LED wall sconces will add a contemporary touch to any home or business. The brushed nickel frame holds a curved opaque lens that is open at the top to allow light to wash the wall above and below. This fixture emits a dimmable 3000K warm white light. Designed for indoor use and UL Listed for damp location installation. With built-in LEDs this attractive fixture will provide up to 30,000 hours of reliable and maintenance free service. Mounting hardware, screws, wire nuts and installation instructions are included.

LED Wall Mount Sconce

Contemporary Design



Steel & Plastic Body
Frosted Lens
Brushed Nickel Finish
90 CRI



Application



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	82111-SU LFX/VF/1L/10W/90CRI/3SCT/BN	10	650	120	30K/40K/50K	50000	DL,DIM	3.35(h)6.75(w)4.1(d)
B	82112-SU LFX/VF/2L/20W/90CRI/3SCT/BN	20	1300	120	30K/40K/50K	50000	DL,DIM	3.35(h)14.85(w)4.1(d)
C	82113-SU LFX/VF/3L/30W/90CRI/3SCT/BN	30	1900	120	30K/40K/50K	50000	DL,DIM	3.35(h)23.0(w)4.1(d)
D	82114-SU LFX/VF/4L/40W/90CRI/3SCT/BN	40	2300	120	30K/40K/50K	50000	DL,DIM	3.35(h)31.1(w)4.1(d)
	82064-SU LFX/WS/4L/40W/D/E/30K	40	2400	120	3000K	50000	DL,DIM	3.35(h)30.7(w)4.1(d)

Steel & Glass Body
Frosted Lens
Brushed Nickel Finish
81 CRI



Application



LED Wall Mount Sconce

Contemporary Design



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
49017-SU	LFX/WS/AR/14/9W/DIM/30K	9	500	120	3000K	50000	DIM	4.2(h) 14.0(w) 3.0(d)
49156-SU	LFX/WS/AR/14/9W/DIM/40K	9	500	120	4000K	50000	DIM	6.5(h) 14.0(w) 3.0(d)



Metal & Acrylic Body
White Lens
Chrome Finish
80 CRI

5
Year
Warranty

Application



LED Wall Sconce Bar / Bath Vanity Light

Contemporary Style



SCT Switch

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
81031-SU	LFX/BAR/REC/2LT/15W/SCT/BN 27"	15	1050	120	27K/30K/35K/40K/50K	50000	DL,DIM	4.8(h) 27.0(w) 3.0(d)

Metal & Acrylic Body
White Lens
Chrome Finish
80 CRI

5
Year
Warranty

Application



LED Wall Sconce Bar / Bath Vanity Light

Contemporary Style



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
81160-SU	LFX/BAR/20W/30K/18"/CH/D/ACRYL	20	1100	120	3000K	50000	DL,DIM	3.5(h) 15.5(w) 4.0(d)
81132-SU	LFX/BAR/20W/SCT/18"/BN/ACRYL	20	1600	120	30K/40K/50K	50000	DL,DIM	3.5(h) 18.5(w) 4.0(d)

LED Wall Sconce Bar / Bath Vanity Light


Etched Glass Shade Cylinder

LED
BUILT-IN

90
CRI



A Smooth



B P-Dot



C P-Fabric



D Brilliant



E Dia-D



F Ballpoint

Metal Body
Smooth Lens
Brushed Nickel Finish
90 CRI

3
Year
Warranty

Application



Hospitality



Commercial



Residential

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A Smooth								
81342-MKS	MKS/BAR/13W/18"/30K/CH/SM	13	1200	120	3000K	30000	DIM	2.0(h) 18.0(w)
81343-MKS	MKS/BAR/13W/18"/40K/CH/SM	13	1200	120	4000K	30000	DIM	2.0(h) 18.0(w)
81354-MKS	MKS/BAR/16W/24"/30K/CH/SM	16	1300	120	3000K	30000	DIM	2.0(h) 24.0(w)
81355-MKS	MKS/BAR/16W/24"/40K/CH/SM	16	1300	120	4000K	30000	DIM	2.0(h) 24.0(w)
B P-Dot								
81344-MKS	MKS/BAR/13W/18"/30K/CH/PD	13	1200	120	3000K	30000	DIM	2.0(h) 18.0(w)
81345-MKS	MKS/BAR/13W/18"/40K/CH/PD	13	1200	120	4000K	30000	DIM	2.0(h) 18.0(w)
81356-MKS	MKS/BAR/16W/24"/30K/CH/PD	16	1300	120	3000K	30000	DIM	2.0(h) 24.0(w)
81357-MKS	MKS/BAR/16W/24"/40K/CH/PD	16	1300	120	4000K	30000	DIM	2.0(h) 24.0(w)
C P-Fabric								
81346-MKS	MKS/BAR/13W/18"/30K/CH/PF	13	1200	120	3000K	30000	DIM	2.0(h) 18.0(w)
81347-MKS	MKS/BAR/13W/18"/40K/CH/PF	13	1200	120	4000K	30000	DIM	2.0(h) 18.0(w)
81358-MKS	MKS/BAR/16W/24"/30K/CH/PF	16	1300	120	3000K	30000	DIM	2.0(h) 24.0(w)
81359-MKS	MKS/BAR/16W/24"/40K/CH/PF	16	1300	120	4000K	30000	DIM	2.0(h) 24.0(w)
D Brilliant								
81348-MKS	MKS/BAR/13W/18"/30K/CH/BT	13	1200	120	3000K	30000	DIM	2.5(h) 18.0(w)
81349-MKS	MKS/BAR/13W/18"/40K/CH/BT	13	1200	120	4000K	30000	DIM	2.5(h) 18.0(w)
81360-MKS	MKS/BAR/16W/24"/30K/CH/BT	16	1300	120	3000K	30000	DIM	2.5(h) 24.0(w)
81361-MKS	MKS/BAR/16W/24"/40K/CH/BT	16	1300	120	4000K	30000	DIM	2.5(h) 24.0(w)
E Dia-D								
81350-MKS	MKS/BAR/13W/18"/30K/CH/DD	13	1200	120	3000K	30000	DIM	2.5(h) 18.0(w)
81351-MKS	MKS/BAR/13W/18"/40K/CH/DD	13	1200	120	4000K	30000	DIM	2.5(h) 18.0(w)
81362-MKS	MKS/BAR/16W/24"/30K/CH/DD	16	1300	120	3000K	30000	DIM	2.5(h) 24.0(w)
81363-MKS	MKS/BAR/16W/24"/40K/CH/DD	16	1300	120	4000K	30000	DIM	2.5(h) 24.0(w)
F Ballpoint								
81352-MKS	MKS/BAR/13W/18"/30K/CH/BP	13	1200	120	3000K	30000	DIM	2.5(h) 18.0(w)
81353-MKS	MKS/BAR/13W/18"/40K/CH/BP	13	1200	120	4000K	30000	DIM	2.5(h) 18.0(w)
81364-MKS	MKS/BAR/16W/24"/30K/CH/BP	16	1300	120	3000K	30000	DIM	2.5(h) 24.0(w)
81365-MKS	MKS/BAR/16W/24"/40K/CH/BP	16	1300	120	4000K	30000	DIM	2.5(h) 24.0(w)




Steel & Acrylic Body
White Lens
Brushed Nickel Finish
80 CRI

5 Year Warranty

Application: Hospitality, Commercial, Residential

LED Wall Sconce Bar / Bath Vanity Light

Modern Contemporary Vanity



A



B

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A 18",24",36" Length Black								
81494-SU	LFX/BAR/15W/SCT/18"/BK	15	1200	100-277	30K/40K/50K	50000	DL,DIM	3.25(h) 18.75(w) 4.75(d)
81376-SU	LFX/BAR/20W/SCT/24"/BK	20	1600	100-277	30K/40K/50K	50000	DL,DIM	2.5(h) 24.0(w) 4.5(d)
81495-SU	LFX/BAR/25W/SCT/36"/BK	25	2000	100-277	30K/40K/50K	50000	DL,DIM	2.5(h)36.0(w) 4.5(d)
81496-SU	LFX/BAR/30W/SCT/48"/BK	30	2400	100-277	30K/40K/50K	50000	DL,DIM	3.25(h)48.75(w) 4.75(d)
B 18",24",36" Length Brush Nickel								
81460-SU	LFX/BAR/20W/18"/BN/SCT	20	1400	100-277	30K/40K/50K	50000	DL,DIM	2.5(h) 18.0(w) 4.5(d)
81461-SU	LFX/BAR/25W/24"/BN/SCT	25	1750	100-277	30K/40K/50K	50000	DL,DIM	2.5(h) 24.0(w) 4.5(d)
81462-SU	LFX/BAR/30W/36"/BN/SCT	30	2100	100-277	30K/40K/50K	50000	DL,DIM	2.5(h) 36.0(w) 4.5(d)

Metal & Acrylic Body
White Lens
Chrome Finish
80 CRI

5 Year Warranty

Application: Hospitality, Commercial, Residential

LED Wall Sconce Bar / Bath Vanity Light

Modern Contemporary Vanity



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
18",24",36" Length Brush Nickel								
85119-SU	LFX/VF/18"/15W/SCT/BN	15	950	120	30K/40K/50K	50000	DL,DIM	4.25(h) 18.0(w) 3.5(d)
85094-SU	LFX/VF/24"/20W/SCT/BN	20	1300	120	30K/40K/50K	50000	DL,DIM	4.25(h) 24.0(w) 3.5(d)
85120-SU	LFX/VF/36"/30W/SCT/BN	30	1950	120	30K/40K/50K	50000	DL,DIM	4.25(h) 36.0(w) 3.5(d)

Sunlite LED Curved Vanity Fixtures will complement any vanity, bathroom or powder room. The brushed nickel finish gives a warm and inviting look while the wide beam angle provides the perfect lighting for daily grooming tasks. Built in, long life LEDs means no bulbs to replace and up to 50,000 hours of reliable use. This dimmable fixture uses 75% less energy than traditional incandescent bulbs. And unlike fluorescent bulbs, LED lights are instant-on at full brightness with no warmup time. Install at home or as a low maintenance commercial lighting solution for hotels, offices, restaurants, retail locations and more. Save time and energy with Sunlite LED Fixtures.

Steel & Acrylic Body
White Lens
Brushed Nickel / Oil Rubbed
Bronze Finish
81 CRI

Options

- 5 Year Warranty
- Battery Backup
- Motion Sensor

Application

Commercial Residential

LED Wall Sconce Bar / Bath Vanity Light

Double Band

LED BUILT-IN

Color Selectable



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	24", 36", 48" Length Brush Nickel Color Selectable							
81491-SU	LFX/VF/24"/3MW/90CRI/3SCT/BN	15W/20W/25W	1420/1895/2370	100-277	30K/40K/50K	50000	DL,DIM	4.33(h) 24.2(w) 5.86(d)
81492-SU	LFX/VF/36"/3MW/90CRI/3SCT/BN	18W/25W/30W	1820/2530/3035	100-277	30K/40K/50K	50000	DL,DIM	4.33(h) 36.0(w) 5.86(d)
81493-SU	LFX/VF/48"/3MW/90CRI/3SCT/BN	28W/35W/40W	2860/3575/4050	100-277	30K/40K/50K	50000	DL,DIM	4.33(h) 47.83(w) 5.86(d)
B	24", 36", 48" Length Oil Rubbed Bronze Color Selectable							
81371-SU	LFX/VF/24"/25W/ORB/SCT	25	2200	120-277	30K/40K/50K	50000	WL,DIM	4.4(h) 24.0(w) 5.9(d)

Steel & Acrylic Body
Acrylic Lens
Brushed Nickel Finish
80 CRI

5 Year Warranty

Application


Hospitality Commercial Residential

LED Wall Sconce Bar / Bath Vanity Light

Modern Contemporary Vanity

LED BUILT-IN

Color Selectable



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)	
A	81381-SU	LFX/BAR/SQ/SG/18"/20W/3SCT/BN	20	1100	120	30K/40K/50K	50000	DL,DIM	3.5(h) 18.0(w) 5.0(d)
B	81341-SU	LFX/BAR/SQ/DG/18"/20W/3SCT/BN	20	1100	120	30K/40K/50K	50000	DL,DIM	6.0(h) 18.0(w) 4.0(d)

Wall Sconce / Bath Vanity Light

Cylinder Sconces

BULB
REQUIRED



A



Up / Down



B



C

Wall Mount
120 volts
Medium (E26) Base
Uses A19 Bulb(s)
Metal Body
UL Listed

Bulb Suggestion



A19
Med E26

Application



Commercial Residential

Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A	81319-SU FIX/VF/1LT/E26/BN/FR	Brushed Nickel	White Glass	1	60	10.0(h) 4.8(w) 5.4(d)
B	81320-SU FIX/VF/2LT/E26/BN/FR	Brushed Nickel	White Glass	2	60	10.0(h) 13.0(w) 5.5(d)
C	81321-SU FIX/VF/3LT/E26/BN/FR	Brushed Nickel	White Glass	3	60	10.0(h) 22.0(w) 5.5(d)

Cone Sconces



A



B



C

Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A	81316-SU FIX/VF/1LT/E26/BN/FR	Brushed Nickel	White Glass	1	60	9.0(h) 5.0(w) 7.0(d)
B	81317-SU FIX/VF/2LT/E26/BN/FR	Brushed Nickel	White Glass	2	60	9.0(h) 16.0(w) 7.0(d)
C	81318-SU FIX/VF/3LT/E26/BN/FR	Brushed Nickel	White Glass	3	60	9.0(h) 24.0(w) 7.0(d)

Square Sconces



A



B



C

Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A	81322-SU FIX/VF/1LT/E26/BN/FR	Brushed Nickel	White Glass	1	60	7.0(h) 5.0(w) 6.0(d)
B	81323-SU FIX/VF/2LT/E26/BN/FR	Brushed Nickel	White Glass	2	60	7.0(h) 16.0(w) 6.0(d)
C	81324-SU FIX/VF/3LT/E26/BN/FR	Brushed Nickel	White Glass	3	60	7.0(h) 24.0(w) 6.0(d)

Wall Sconce / Bath Vanity Light

Decorative Sconces

BULB
REQUIRED




Wall Mount
120 volts
Medium (E26) Base
Uses A19 Bulb(s)
Metal & Glass Body
UL Listed

Bulb Suggestion



Application



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A	45055-SU FIX/FM/BATH/1LT/E26/BN/FR	Brushed Nickel	Frosted Glass	1	100	7.0(h) 5.5(w) 7.8(d)
B	45056-SU FIX/FM/BATH/2LT/E26/BN/FR	Brushed Nickel	Frosted Glass	2	100	7.0(h) 6.3(w) 17.0(d)
C	45057-SU FIX/FM/BATH/3LT/E26/BN/FR	Brushed Nickel	Frosted Glass	3	100	7.0(h) 6.3(w) 24.0(d)
D	45058-SU FIX/FM/BATH/4LT/E26/BN/FR	Brushed Nickel	Frosted Glass	4	100	7.0(h) 6.3(w) 30.0(d)



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A	45059-SU FIX/SM/BATH/3LT/E26/BN/WH	Brushed Nickel	White Glass	3	100	8.5(h) 6.0(w) 24.0(d)
B	45060-SU FIX/SM/BATH/4LT/E26/BN/WH	Brushed Nickel	White Glass	4	100	8.5(h) 6.0(w) 33.5(d)



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A	46061-SU FIX/SQ/BATH/1LT/E26/BN/FR	Brushed Nickel	Frosted Glass	1	100	4.3(h) 4.3(w) 4.3(d)
B	46062-SU FIX/SQ/BATH/2LT/E26/BN/FR	Brushed Nickel	Frosted Glass	2	100	8.8(h) 5.0(w) 14.0(d)
C	46063-SU FIX/SQ/BATH/3LT/E26/BN/FR	Brushed Nickel	Frosted Glass	3	100	8.8(h) 5.0(w) 20.0(d)
D	46064-SU FIX/SQ/BATH/4LT/E26/BN/FR	Brushed Nickel	Frosted Glass	4	100	8.8(h) 5.0(w) 25.6(d)

120 volts
Medium (E26) Base
Uses A19 Bulb(s)
Metal & Glass Body
UL Listed
Bulb Not Included

Bulb Suggestion



Wall Sconce / Bath Vanity Light

Classic style

**BULB
REQUIRED**



Up / Down



Application



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
Brushed Nickel						
45430-SU	B214/BN/AL	Brushed Nickel	Alabaster Glass	2	60	9.5(h) 5.5(w) 14.0(d)
45405-SU	B324U/BN/AL	Brushed Nickel	Alabaster Glass	3	60	8.3(h) 5.5(w) 24.0(d)
45445-SU	B648D/BN/AL	Brushed Nickel	Alabaster Glass	6	60	9.5(h) 5.5(w) 48.0(d)



A Brushed Nickel B Chrome



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A Brushed Nickel						
45000-SU	B318/BN	Brushed Nickel	-	3	60	4.9(h) 2.3(w) 18.0(d)
45100-SU	B424/BN	Brushed Nickel	-	4	60	4.9(h) 2.3(w) 24.0(d)
41308-SU	B636/BN	Brushed Nickel	-	6	60	4.9(h) 2.3(w) 35.8(d)
45300-SU	B848/BN	Brushed Nickel	-	8	60	4.9(h) 2.3(w) 48.0(d)
B Chrome						
45025-SU	B318/CH	Chrome	-	3	60	4.9(h) 2.3(w) 18.0(d)
45125-SU	B424/CH	Chrome	-	4	60	4.9(h) 2.3(w) 24.0(d)
45325-SU	B848/CH	Chrome	-	8	60	4.9(h) 23 (w) 48.0(d)

Wall Mount
120 volts
Medium (E26) Base
Metal Body / Glass Lens
Polished Brass Finish
UL Listed
Bulb Not Included

Bulb Suggestion



Wall Mount Sconce

Tulip Shaped

**BULB
REQUIRED**



Application



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
04530-SU	TUL	Polished Brass	Glass	1	60	7.75(h) 4.5(w) 5.5(d)

120 volts
G9 Base
Metal Body
White Glass Lens
ETL Listed
Bulb Not Included

Bulb Suggestion



G9
Bi Pin

Application



Wall Sconce

3 Lights

**BULB
REQUIRED**



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
46056-SU	FIX/VF/3LT/G9/AB	Black	Glass	3	4	5.0(h) 15.0(w) 5.0(d)

120 volts
G9 Base
Metal Body
Polished Nickel Finish
ETL Listed
Bulb Not Included

Bulb Suggestion



G9
Bi Pin

Application



Wall Sconce

Steel Swirl

**BULB
REQUIRED**



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
46059-SU	FIX/SWIRL/G9	Brushed Nickel	-	1	4	9.75(h) 4.75(w) 3.75(d)

Wall Mount
120 volts
Medium (E26) Base
Bronze Finish
Metal Body / Glass Lens
ETL Listed
Bulb Not Included

Bulb Suggestion



A19
Med E26

Application



Wall Mount Sconce

Modern Style

**BULB
REQUIRED**



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
45062-SU	FIX/WS/TD/BRZ	Bronze	Glass	1	60	11.75(h) 5.0(w) 6.5(d)

Wall Sconce

Antique Style

BULB
REQUIRED



A



B



C




D



E



F



Wall Mount
120 volts
Medium (E26) Base
Metal Body
UL Listed
Bulb Not Included

Bulb Suggestion



Application



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)	
A	07054-SU	AQF/WCC/OB	Oil Black	Transparent Glass	1	40	10.8(h) 6.5(w) 12.0(d)
B	07056-SU	AQF/OWC/OB	Vintage Oil Bronze	-	1	40	14.2(h) 6.5(w) 8.8(d)
C	07036-SU	AQF/WC/AB	Antique Brass	-	1	60	10.8(h) 8.7(w) 10.3(d)
D	07040-SU	AQF/2WT/AB	Antique Black	-	2	60	13.1(h) 4.1(w) 11.8(d)
E	07038-SU	AQF/WTP/IR	Black	-	1	60	18.1(h) 4.4(w) 4.6(d)
F	07076-SU	AQF/PS/IR	Iron Rust	-	5	40	20.0(h) 5.0(w) 42.0(d)



Outdoor

Light Fixtures

Sunlite's outdoor wall sconces provide elegant illumination. Its durable aluminum matte black finish guarantees you a long-lasting attractive light fixture that will stand the test of time. Use this fixture indoors and outdoors. It can be placed in the garage, garden, corridor, patio, hallway, balcony, or walkway. It lights up the dark and is also a beautiful decorative piece with an elegant appearance, making it a great choice!

Aluminum & Steel Body
Glass Lens
Black / Oil Rubbed Bronze Finish
80 CRI

5
Year
Warranty

Application



LED Outdoor Wall Sconce

Square Cube Up & Down



Square
(Up and Down Light)

Square
(UP or Down Light)

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
Square Up/Down								
81292-SU	LFX/CUBE/UD/18W/SCT/BK	18	1300	120	30/40K/50K	50000	WL	4.0(h) 3.75(w) 4.3(d)
81298-SU	LFX/CUBE/UD/18W/30K/BK	18	1300	120	3000K	50000	WL	4.0(h) 3.75(w) 4.3(d)
81299-SU	LFX/CUBE/UD/18W/50K/BK	18	1300	120	5000K	50000	WL	4.0(h) 3.75(w) 4.3(d)
Square Down								
81291-SU	LFX/CUBE/S/9W/SCT/BK	9	650	120	30/40K/50K	50000	WL	4.0(h) 3.75(w) 4.3(d)
Square Down (Oil Rubbed Bronze Finish)								
81293-SU	LFX/CUBE/S/9W/30K/ORB	9	650	120	3000K	50000	WL	4.0(h) 3.75(w) 4.3(d)



Aluminum Body
Clear Lens
Matte Black Finish
80 CRI

5
Year
Warranty

Application



LED Outdoor Wall Sconce

Cube Up & Down



Sunlite LED Rectangular Decorative Wall Washer Fixtures are designed to provide outdoor illumination for a variety of residential and commercial applications. These up and down light fixtures wash the wall above and below with light. They are dimmable and provide a bright 300 lumen output at a 3000K warm white color temperature. Built-in LEDs make them an energy efficient and maintenance-free lighting solution with a long life span of up to 50,000 hours. Each fixture uses only 6 watts of electricity and has an estimated yearly energy cost of \$0.72. (Based on 3 hours/day use at \$0.11/kWh) The weather-resistant aluminum body has a matte black finish. This outdoor fixture is ideal for anywhere extra lighting is needed. ETL Listed for wet location installation.



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
81307-SU	LFX/CUBE/6W/30K/BL/UD	6	300	120	3000K	50000	WL,DIM	7.1(h) 5.5(w) 4.1(d)

This Sunlite LED Decorative Wall Light fixture is as attractive as it is functional. With a weather-proof aluminum body and built-in 50,000 hour life LEDs this fixture is designed for years of efficient and maintenance free service. Matte black finish and modern design ideal for use on porches, walls, next to doors and garages, on gate posts, or any outdoor space. Hardware and instructions for mounting on any standard junction box included. ETL Listed for wet location installation.



Aluminum Body
Clear Lens
Black Finish
80 CRI

5
Year
Warranty

Application



LED Outdoor Wall Sconce

Up & Down



A
Round
(Up and Down Light)



B
Square
(Up and Down Light)



C
Square
(UP or Down Light)

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	Round Up and Down							
88142-SU	LFX/UD/R/12"/24W/BK/SCT	24	1700	120-277	30K/40K/50K	50000	WL	11.9(h) 4.3(w) 6.9(d)
B	Square Up and Down							
88143-SU	LFX/UD/SQ/24W/SCT/MV/BK/10"	12	1700	120-277	30K/40K/50K	50000	WL	10.3(h) 3.5(w) 6.1(d)
C	Square Up or Down							
88134-SU	LFX/D/SQ/8"/12W/SCT/BK	12	850	120	30K/40K/50K	50000	WL	8.1(h) 4.4(w) 6.1(d)

Sunlite's outdoor wall sconces features the perfect balance between vintage and modern aesthetics that perfectly blends in with both the high-end and everyday home's front porch/veranda, to the backyard. Its durable yet chic brushed nickel steel construction guarantees you a long lasting attractive light fixture that will stand the test of time.

Steel & Glass Body
Clear Lens
Brushed Nickel Finish
80 CRI

5
Year
Warranty

Application



LED Outdoor Wall Sconce

Cylinder Up & Down

LED
BUILT-IN



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	49204-SU LFX/DOD/T/6/12W/3SCT/BN	12	1000	120	30K/40K/50K	50000	WL,DIM	6.0(h) 4.35(w) 4.3(d)
B	49205-SU LFX/DOD/T/8/24W/3SCT/BN	24	1800	120	30K/40K/50K	50000	WL,DIM	8.1(h) 4.35(w) 4.3(d)



Aluminum Body
Clear Seedy Lens
Black Finish
80 CRI

5
Year
Warranty

Application



LED Outdoor Wall Sconce

Seedy Glass Design

LED
BUILT-IN



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	81041-SU LFX/WS/SEEDY/CYL/12"/10W/SCT/BK	10	600	120	30K/40K/50K	50000	WL,DIM	12.0(h) 4.75(w) 4.0(d)
B	81330-SU LFX/WS/CL/10W/CRI90/3SCT/BK	15	800	120	30K/40K/50K	50000	WL,DIM	12.0(h) 5.5(w) 4.0(d)
C	81227-SU LFX/TERR/WS/4"/12W/3SCT/ORB/SEEDY	12	500	120	30K/40K/50K	50000	WL,DIM	14.0(h) 4.75(w) 4.25(d)

This Sunlite LED Decorative Wall Light fixture is as attractive as it is functional. With a weather-proof aluminum body and built-in 50,000 hour life LEDs this fixture is designed for years of efficient and maintenance free service. Matte black finish and modern design ideal for use on porches, walls, next to doors and garages, on gate posts, or any outdoor space. Hardware and instructions for mounting on any standard junction box included. ETL Listed for wet location installation. These Energy Star Certified fixtures may qualify you for state and local energy rebates.

Aluminum Body
Clear Lens
Black Finish
80 CRI

5
 Year
 Warranty

Application



LED Outdoor Wall Sconce

Cylinder Up & Down



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
Up/Down Color Selectable								
A	81294-SU LFX/UD/HC/12W/MV/SCT/BK	12	1200	120-277	30K/40K/50K	50000	WL,DIM	9.25(h) 4.5(w) 5.25(d)
B	81295-SU LFX/UD/REC/12W/MV/SCT/BK	12	1200	120-277	30K/40K/50K	50000	WL,DIM	9.13(h) 4.5(w) 5.25(d)



Metal Body
Crystal Glass Lens
Black Finish
80 CRI

5
 Year
 Warranty

Application



LED Outdoor Wall Sconce

Crystal Glass Design



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
81038-SU	LFX/WS/XTL/12"/10W/SCT/BK	10	800	120	30K/40K/50K	50000	DL,DIM	11.0(h) 5.5(w) 3.0(d)

LED Outdoor Wall Sconce

Seedy Glass Design

With built in LED lights this Sunlite wall sconce is designed to provide years of maintenance-free use in residential or commercial locations. The elegant metal body with matte black finish holds a unique raindrop glass panel. The hidden LEDs refract through the drops in the panel creating a brilliant and peaceful glow. Designed for indoor or outdoor installation. This stylish and practical fixture is ideal for illuminating foyers, entrance ways, common areas, and balconies. The ADA Compliant design allows for installation in commercial and public spaces requiring handicapped accessibility. ETL Listed for wet location installation. Mounting hardware and installation instructions included.



Glass Body
Clear Seedy Lens
Black Finish
80 CRI

5
Year
Warranty

Application



Hospitality



Retail



Commercial




Residential

LED
BUILT-IN



A



B

C

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
5" Width								
A	81046-SU LFX/WS/SEEDY/UD/12"/11W/30K/BK	11	600	120	3000K	50000	WL,DIM	7.0(h) 5.0(w) 1.5(d)
B	81222-SU LFX/INN/WS/5"/9W/50K/BK/SEEDY	9	450	100-277	5000K	50000	WL	13.8(h) 4.8(w) 2.5(d)
	81047-SU LFX/INN/WS/5"/12W/SCT/BK/SEEDY	12	600	120	30K/40K/50K	50000	WL	13.8(h) 4.8(w) 2.5(d)
C 6.5" Width								
	81051-SU LFX/INN/WS/6.5"/12W/SCT/BK/SEEDY	12	600	120	30K/40K/50K	50000	WL	13.8(h) 6.5(w) 2.5(d)
	81170-SU LFX/INN/WS/6.5"/12W/30K/BK/SEEDY	12	600	100-277	3000K	50000	WL	13.8(h) 6.5(w) 2.5(d)
	81223-SU LFX/INN/WS/6.5"/12W/50K/BK/SEEDY	12	600	100-277	5000K	50000	WL	13.8(h) 6.5(w) 2.5(d)



LED Outdoor Wall Sconce

Seedy Glass Design



With built in LED lights this Sunlite wall sconce is designed to provide years of maintenance-free use in residential or commercial locations. The elegant metal body with matte black finish holds a unique raindrop glass panel. The hidden LEDs refract through the drops in the panel creating a brilliant and peaceful glow. Designed for indoor or outdoor installation. This stylish and practical fixture is ideal for illuminating foyers, entrance ways, common areas, and balconies. Mounting hardware and installation instructions included.

<p>Aluminum Body Clear Seedy Lens Black Finish 80 CRI</p>	<p>5 Year Warranty</p>
<p>Application</p>	<p>Hospitality Commercial Residential</p>



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	81039-SU LFX/WS/SEEDY/UD/A/12"/22W/30K/BK	22	300	120	3000K	50000	WL,DIM	12.0(h) 5.5(w) 2.5(d)
B	81040-SU LFX/WS/SEEDY/UD/B/12"/22W/30K/BK	22	300	120	3000K	50000	WL,DIM	12.0(h) 5.5(w) 2.5(d)
C	81205-SU LFX/WS/SEEDY/UD/12"/22W/30K/BK	22	300	120	3000K	50000	WL,DIM	12.0(h) 5.5(w) 2.5(d)

Specifications may change without notice. We are not responsible for any typographical errors

LED Outdoor Wall Sconce


Contemporary Style



Aluminum Body
Acrylic Lens
Black / White Finish
90 CRI

3
Year
Warranty

Application



A



B



C



D



E



F



G



H

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	85104-SU LFX/WS/R/12W/SCT/BK	12	850	120	30K/40K/50K	50000	WL	6.7(h) 6.7(w) 4.0(d)
B	85105-SU LFX/WS/R/12W/SCT/WH	12	850	120	30K/40K/50K	50000	WL	6.7(h) 6.7(w) 4.0(d)
C	85106-SU LFX/WS/RC/12W/SCT/BK	12	850	120	30K/40K/50K	50000	WL	6.7(h) 6.7(w) 4.0(d)
D	85109-SU LFX/WS/RC/12W/SCT/WH	12	850	120	30K/40K/50K	50000	WL	6.7(h) 6.7(w) 4.0(d)
E	85113-SU LFX/WS/SQC/12W/SCT/BK	12	850	120	30K/40K/50K	50000	WL	6.3(h) 6.3(w) 4.0(d)
F	85114-SU LFX/WS/SQC/12W/SCT/WH	12	850	120	30K/40K/50K	50000	WL	6.3(h) 6.3(w) 4.0(d)
G	85110-SU LFX/WS/SQ/12W/SCT/BK	12	850	120	30K/40K/50K	50000	WL	6.3(h) 6.3(w) 4.0(d)
H	85112-SU LFX/WS/SQ/12W/SCT/WH	12	850	120	30K/40K/50K	50000	WL	6.3(h) 6.3(w) 4.0(d)

Add a modern touch to any home or business with this Sunlite LED wall sconce. The contemporary design oil rubbed bronze frame holds an opaque white polycarbonate lens. Built in LEDs makes this a no maintenance lighting solution for home or commercial use. Suitable for indoor or outdoor use, this attractive fixture will provide up to 50,000 hours of reliable service. Mounting bracket, screws, wire nuts and installation instructions are included.

Metal Body
White Lens
Silver / Oil Rubbed Bronze Finish
80 CRI


5
 Year
 Warranty

Application



LED Outdoor Wall Sconce

Contemporary Style



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	8" Height							
88673-SU	LFX/CONT/WS/8"/12W/SCT/ORB/ACRY	12	600	100-277	30K/40K/50K	50000	WL	8.0(h) 6.0(w) 4.0(d)
81480-SU	LFX/CONT/WS/8"/12W/SCT/SL/ACRY	12	600	100-277	30K/40K/50K	50000	WL	8.0(h) 6.0(w) 4.0(d)
B	14" Height							
81482-SU	LFX/CONT/WS/14"/20W/SCT/SL/ACRY	20	1100	100-277	30K/40K/50K	50000	WL	14.0(h) 5.9(w) 3.2(d)
81481-SU	LFX/CONT/WS/14"/20W/SCT/ORB/ACRY	20	1100	100-277	30K/40K/50K	50000	WL	14.0(h) 5.9(w) 3.2(d)

Metal Body
White Glass Lens
Black Finish
80 CRI

5
 Year
 Warranty

Application



LED Outdoor Wall Sconce

Contemporary Design



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
81032-SU	LFX/WS/KNOB/15W/30K/BK	15	800	120	3000K	50000	WLL,DIM	12.0(h) 5.5(w) 4.0(d)

Aluminum & Plastic Body
White Lens
Oil Rubbed Bronze Finish
81 CRI

5
 Year
 Warranty

Application



LED Outdoor Wall Sconce

Half Cylinder



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
82023-SU	LFX/HC/ORB/15W/SCT	15	950	120	30K/40K/50K	50000	WL,DIM,ES	10.0(h) 7.0(w) 3.0(d)

LED Outdoor Wall Sconce

Vintage Style



Add a classic touch to any home or business with these Sunlite LED Wall Sconces. The Mission-style design black metal frame holds an opaque white lens. Built in LEDs makes this a no maintenance lighting solution for home or commercial use. Suitable for indoor or outdoor use. Available in four sizes from 12 to 30 inches. Mounting hardware, screws, wire nuts and installation instructions are included.



A
12"



B
18"



C
24"



D
30"

Metal Body
Acrylic White Lens
Black / Bronze Finish
80 CRI

Options



Application



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	12" Height							
81434-SU	LFX/AQ/WS/12"/15W/SCT/BK/ACRY	15	800	100-277	30K/40K/50K	50000	WL	12.0(h) 6.0(w) 4.0(d)
B	18" Height							
81435-SU	LFX/AQ/WS/18"/20W/SCT/BK/ACRY	20	1000	100-277	30K/40K/50K	50000	WL	18.0(h) 6.0(w) 4.0(d)
C	24" Height							
81436-SU	LFX/AQ/WS/24"/23W/SCT/BK/ACRY	23	1200	100-277	30K/40K/50K	50000	WL	24.0(h) 6.0(w) 4.0(d)
D	30" Height Bronze Finish							
91167-SU	LFX/AQ/WS/30"/28W/SCT/BRZ/ACRY	28	1400	100-277	30K/40K/50K	50000	WL	30.0(h) 6.0(w) 4.0(d)

LED Outdoor Wall Sconce

Vintage Style



Add a classic touch to any home or business with these Sunlite Selectable LED Wall Fixtures. These Selectable fixtures feature innovative technology that allows you to choose the color temperature at the time of installation. Select 3000K Warm White, 4000K Cool White, or 5000K Super White depending on your preference using a switch located on the back. With energy efficient LEDs these are a no maintenance lighting solution for residential or commercial use. Long 50,000 hour lifespan for years of maintenance-free service. ETL Listed for wet location installation.



Aluminum & Steel Body
White Lens
Black Finish
Built-in Photocell
80 CRI



Application



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	88682-SU LFX/WS/SCT/HC/12W/BK/PC	12	800	120	30K/40K/50K	50000	WL	10.0(h) 10.3(w) 4.0(d)
B	88686-SU LFX/WS/SCT/RT/12W/TG/BK/PC	12	800	120	30K/40K/50K	50000	WL	9.4(h) 8.5(w) 5.0(d)
C	88680-SU LFX/WS/SCT/HH/12W/BK/PC	12	800	120	30K/40K/50K	50000	WL	12.1(h) 8.0(w) 5.7(d)
D	88681-SU LFX/WS/SCT/HO/12W/BK/PC	12	800	120	30K/40K/50K	50000	WL	9.8(h) 7.8(w) 4.1(d)
E	88683-SU LFX/WS/SCT/RT/12W/SG/BK/PC	12	800	120	30K/40K/50K	50000	WL	9.5(h) 8.0(w) 4.5(d)
F	88687-SU LFX/WS/SCT/LN/9W/BK/PC	9	600	120	30K/40K/50K	50000	WL	11.8(h) 6.1(w) 8.1(d)

Aluminum & Steel Body
White Lens
Black Finish
80 CRI

5
Year
Warranty

Application



LED Outdoor Wall Sconce

Vintage Style

LED
BUILT-IN



A



B

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	88684-SU LFX/WS/SCT/LN/12W/BK	12	800	120	30K/40K/50K	50000	WL	8.7(h) 8.8(w) 10.3(d)
B	88688-SU LFX/WS/SCT/HCL/9W/GL/BK	9	600	120	30K/40K/50K	50000	WL	9.8(h) 7.3(w) 3.7(d)

Aluminum & Steel Body
White Lens
Black Finish
80 CRI

5
Year
Warranty

Application



LED Outdoor Wall Sconce

Wall Lantern Design

LED
BUILT-IN



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
I	81300-SU LFX/WS/CL/9W/MV/SCT/BK	9	900	120	30K/40K/50K	50000	WL	13.8(h) 7.3(w) 9.5(d)

Steel Body
Amber Lens
Copper Bronze Finish
81 CRI

5
Year
Warranty

Application



LED Outdoor Wall Sconce

Wall Lantern Design

LED
BUILT-IN



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
49025-SU	LFX/DOD/L/6/12W/30K	12	400	120	3000K	35000	WL	12.5(h) 6.0(w) 7.5(d)
49026-SU	LFX/DOD/L/8/15W/30K	15	500	120	3000K	35000	WL	16.0(h) 4.5(w) 9.0(d)

Outdoor Post Mounted Fixture

Globe Style

BULB
REQUIRED

 Polycarbonate



A



B



C



D



E



F



Pole Mount

120 volts

Medium (E26) Base

Uses A19 Bulb

Polycarbonate Body

UL Listed—Wet Location

Fit Most 3" Diameter Posts (Not Included)

Bulb Suggestion



A19
Med E26

Application



Commercial



Residential



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
10" Inch						
A	47242-SU DOD/10GL/BK/WH/MED	Black	White Acrylic	1	100	12.8(w) 10.0(d)
B	47244-SU DOD/10GL/WH/WH/MED	White	White Acrylic	1	100	12.8(w) 10.0(d)
C	47246-SU DOD/10GL/BK/CL/MED	Black	Clear Acrylic	1	100	12.8(w) 10.0(d)
12" Inch						
D	41324-SU DOD/12GL/BK/WH/MED	White	White Acrylic	1	100	12.0(w) 12.0(d)
E	41320-SU DOD/12GL/WH/WH/MED	Black	White Acrylic	1	100	12.0(w) 12.0(d)
F	41321-SU DOD/12GL/BK/CL/MED	Black	Clear Acrylic	1	100	12.0(w) 12.0(d)

120 volts
 Medium (E26) Base
 Uses A19 Bulb
 Polycarbonate Body
 UL Listed–Wet Location
 Fit Most 3" Diameter Posts (Not Included)

Bulb Suggestion



Outdoor Post Mounted Fixture

Orchid Style Collection

BULB
 REQUIRED

Polycarbonate



Application



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
Medium Base						
47218-SU	DOD/ORP/WH/CL/MED	White	Clear Acrylic	1	60	16.0(h) 8.0(w) 8.0(d)
GU24 Base						
48222-SU	DOD/ORP/WH/FR/GU24	White	White Acrylic	1	18	16.0(h) 8.0(w) 8.0(d)



LED Outdoor Wall Sconce

Porch Lighting

LED
 BUILT-IN



Aluminum Body
 White Lens
 Black Finish
 80 CRI



Application



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
85103-SU	LFX/BH/12W/SCT/BK	12	650	120	30K/40K/50K	50000	WL	11.8(h)7.4(w) 3.7(d)



Polycarbonate Body
White Lens
Black / White Finish
74 CRI

3
Year
Warranty

Application

Landscape Commercial Residential

LED Outdoor Wall Sconce

Round And Oval Euro Design



A




B

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	49000-SU LFX/DOD/EBL/BK/FR/40K	11.3	1000	120	4000K	50000	WL,ES	5.0(h) 6.0(w) 10.0(d)
B	49004-SU LFX/DOD/EL/BK/FR/120V/40K	23	1900	120	4000K	50000	WL,ES	5.4(w) 10.0(d)

Wall Mount
120 volts
Medium (E26) Base
Uses A19 Bulb
Polycarbonate Body
UL Listed - Wet Location

Bulb Suggestion



A19
Med E26

Application

Commercial Residential

LED Outdoor Wall Sconce

Round And Oval Euro Design



A



B




C

Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A	47212-SU DOD/EG/BK/FR/MED	Black	Polycarbonate	1	75	10.25(w) 10.25(d)
B	47214-SU DOD/EG/WH/FR/MED	White	Polycarbonate	1	75	10.25(w) 10.25(d)
C	47206-SU DOD/EBL/WH/FR/MED	White	Polycarbonate	1	60	6.0(h) 4.25(w) 10.6(d)



Wall Mount
 120 volts
 Medium (E26) Base
 Uses A19 Bulb
 Polycarbonate Body
 UL Listed–Wet Location

Bulb Suggestion



A19
Med E26

Application

Commercial Residential

Outdoor Wall Sconce

Nautical Style

**BULB
REQUIRED**

 Polycarbonate



A





B

Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A 41370-SU	DOD/NC/BK/CL/MED	Black	White Acrylic	1	60	13.0(h) 11.0(w) 10.1(d)
B 41367-SU	DOD/NC/WH/CL/MED	White	White Acrylic	1	60	11.0(h) 11.0(w) 10.1(d)





Pole Mount
 120 volts
 Medium (E26) Base
 Uses A19 Bulb
 Polycarbonate Body
 UL Listed–Wet Location

Bulb Suggestion

A19 Med E26 A19 GU 24

Application

Commercial Residential

Outdoor Wall Sconce

Orchid Style Collection

**BULB
REQUIRED**

 Polycarbonate



A
Down Fixture



B
Up Fixture

Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A 47222-SU	Down Fixture Medium Base DOD/ORD/WH/CL/MED	White	Clear Acrylic	1	60	10.5(h) 6.5(w) 6.5(d)
48226-SU	Down Fixture GU24 Base DOD/ORD/WH/FR/GU24	White	White Acrylic	1	18	10.5(h) 6.5(w) 6.5(d)
B 47226-SU	Up Fixture Medium Base DOD/ORU/WH/CL/MED	White	Clear Acrylic	1	60	16.0(h) 8.0(w) 8.0(d)
48230-SU	Up Fixture GU24 Base DOD/ORU/WH/FR/GU24	White	White Acrylic	1	18	16.0(h) 8.0(w) 8.0(d)

120 volts
 Medium (E26) Base
 Uses A19 Bulb(s)
 Metal & Glass Body
 UL Listed

Bulb Suggestion



Application

Outdoor Wall Mount Fixture

Carriage & Coach Style Collection

**BULB
 REQUIRED**



A
Up Style



B
Down Style

Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A	47130-SU ODI1130/BK	Black	Clear Glass	1	60	14.0(h) 6.0(w) 7.8(d)
B	47120-SU ODI1120/WH	White	Clear Glass	1	60	16.4(h) 6.3(w) 7.5(d)

120 volts
 Medium (E26) Base
 Uses A19 Bulb(s)
 Aluminum Body
 ETL –Wet Location

Bulb Suggestion



Application

Outdoor Wall Mount Fixture

Rectangle

**BULB
 REQUIRED**



A



B



C




D

Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A	46092-SU FIX/WS/E26/BLACK	Black Powder	Opal PC	1	60	4.1(h) 6.7(w) 11.8(d)
B	46091-SU FIX/WS/E26/SS	Brushed Nickel	Opal PC	1	60	4.1(h) 6.7(w) 11.8(d)
C	46093-SU FIX/WS/E26/BLACK	Black Powder	Opal PC	1	60	4.1(h) 6.7(w) 11.8(d)
D	46094-SU FIX/WS/E26/SS	Brushed Nickel	Opal PC	1	60	4.1(h) 6.7(w) 11.8(d)



120 volts
Medium (E26) Base
Metal & Glass Body
UL Listed

Bulb Suggestion



A19
Med E26

Application

Commercial Residential

Outdoor Wall Mount Fixture

Buckhead



**BULB
REQUIRED**



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A	47020-SU ODI1020/BK	Black	Frosted Glass	1	100	12.0(h) 4.1(w) 4.4(d)
B	47030-SU ODI1030/WH	White	Frosted Glass	1	100	8.7(h) 4.1(w) 4.4(d)

120 volts
Medium (E26) Base
Metal Body
Black Finish
ETL Listed




Bulb Suggestion

PAR30
Med E26

A19
Med E26

Application

Hospitality Retail Residential

Outdoor Wall Mount Fixture

Modern Style



**BULB
REQUIRED**



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
90158-SU	FIX/CWS/E26/BK	Black	-	1	75	4.38(h) 7.25(w) 7.0(d)

120 volts
Med (E26) / G24q1 Base
Metal & Glass Body
UL Listed



Bulb Suggestion

A19
Med E26

PLD
G24Q1

Application

Commercial Residential

Outdoor Wall Mount Fixture

Globe / Jar Style

**BULB
REQUIRED**



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
Medium Base						
A	47040-SU ODI1040/BK/E26	Black	Clear Glass	1	100	7.5(h) 4.5(w) 5.8(d)
B	47050-SU ODI1050/WH/E26	White	Clear Glass	1	100	7.5(h) 4.5(w) 5.8(d)
C	47000-SU ODI1000/BK/E26	Black	White Glass	1	60	7.7(h) 6.0(w) 6.7(d)
G24q1 Base CFL Bulb Included						
D	48030-SU ODF1015/WH	White	White Glass	1	13 PLD	7.7(h) 6.0(w) 6.9(d)

LED Outdoor Gooseneck Fixture

Wall Mount

LED
BUILT-IN

The Sunlite LED Gooseneck Barn Fixture brings a rustic design element to your home or business. No bulbs to replace. Built-in LEDs with a 50,000 hour life span makes this a maintenance-free lighting solution for years to come. This weather-proof outdoor fixture is ETL Listed for wet location installation, but can also be installed indoors for a rustic farmhouse look. It's finished in matte black and can be installed on any standard junction box. This fixture is dimmable when attached to a compatible dimmer. Light output is 3000K (warm white) at 700 lumens using only 12 watts of electricity. Estimated Annual Energy Cost is \$1.45 based on 3 hours/day use at \$0.11/kWh. Fixture measures 15.38 in (H), 11 in (W), 12 in (D).

Steel Body
Matte Black Finish
80 CRI

5
Year
Warranty



Application



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
81315-SU	LFX/GN/12W/30/BK	12	700	120	3000K	50000	WL,DIM	12.0(w) 15.0(d)

120 volts
Medium (E26) Base
Uses A19 Bulb(s)
Metal Body
UL Listed—Wet Location
Bulb Not Included

Bulb Suggestion



Outdoor Gooseneck Fixture

Wall Mount

BULB
REQUIRED

Application



A



B



C

Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A 46067-SU	FIX/GN/E26/BLACK	Black	-	1	60	11.5(h) 12.0(w) 15.0(d)
B 46069-SU	FIX/GN/E26/RED	Red	-	1	60	11.5(h) 12.0(w) 15.0(d)
C 46068-SU	FIX/GN/E26/WHITE	White	-	1	60	11.5(h) 12.0(w) 15.0(d)

SunliteLED Wall Mount Floodlight fixtures provide ample illumination for all outdoor spaces. Dual heads can be adjusted individually to optimize coverage area. Built-in motion sensor activates lights when movement is detected. Long life, LED technology built-in means no bulbs to replace and up to 35,000 hours of maintenance-free service. ETL Listed for wet location installation and IP65 rated.

Plastic Body
Clear Lens
Black Finish
Built-in Photocell & Motion Sensor
80 CRI



Application



LED Outdoor Security Flood Light

Motion Sensor

LED
BUILT-IN



A

B



C



D



E

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
2 Head Round Style 1								
A	88907-SU LFX/OSF/R/MS/20W/50K/BK	20	1800	120	5000K	35000	WL	9.3(h) 6.3(w) 7.6(d)
B	88909-SU LFX/OSF/R/MS/20W/50K/WH	20	1800	120	5000K	35000	WL	9.3(h) 6.3(w) 7.6(d)
2 Head Round Style 2								
C	88906-SU LFX/OSF/R/MS/20W/30K/BK	20	1800	120	3000K	35000	WL	9.3(h) 6.3(w) 7.6(d)
D	88908-SU LFX/OSF/R/MS/20W/30K/WH	20	1800	120	3000K	35000	WL	9.3(h) 6.3(w) 7.6(d)
2 Head Square								
E	88911-SU LFX/OSF/S/MS/24W/30K/BK	24	2400	120	3000K	35000	WL	11.9(h) 6.1(w) 5.9(d)
	88912-SU LFX/OSF/S/MS/24W/50K/BK	24	2400	120	5000K	35000	WL	11.9(h) 6.1(w) 5.9(d)

120 volts
Medium (E26) Base
Uses PAR38 Bulb(s)
UL Listed

Bulb Suggestion



PAR38
Med E26

A19
Med E26

Application



Outdoor Security Flood Light

BULB
REQUIRED



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
04918-SU	PL2H/WH	White	-	2	60	4.3(h) 4.3(w) 8.5(d)

120 volts
 Medium (E26) Base
 Uses A19 Bulb(s)
 Metal & Glass Body
 UL Listed
 Fit Most 3" Diameter Posts (Not Included)

Bulb Suggestion



Application

Outdoor Post Mounted Fixture

Carriage & Coach Style Collection

**BULB
 REQUIRED**



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A 41322-SU	ODI1150/BK	Black	Clear Glass	1	60	12.4(h) 5.9(w) 5.9(d)
B 41323-SU	ODI1160/WH	White	Clear Glass	1	60	12.1(h) 5.9(w) 5.9(d)



LED Outdoor Ceiling Flush Mount

Octagonal Design

**LED
 BUILT-IN**



Aluminum Body
 Frosted Lens
 Black Finish
 80 CRI



Application

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
87787-SU	LFX/OOF/17W/SCT/BK	17	800	120	30K/40K/50K	50000	WL,DIM	4.75(w) 12(d)

Specifications may change without notice.
 We are not responsible for any typographical errors

Aluminum Body
Clear Lens
Bronze Finish
80 CRI

Options

- 5 Year Warranty
- Battery Backup
- Motion Sensor


Application

- Industrial
- Commercial
- Residential

LED Outdoor Wall Mount Series

Wall Pack

Sunlite LED Large Wall Pack fixtures are designed to provide ample outdoor illumination. The weather-resistant metal body is finished in bronze and houses a durable glass lens. Ideal for security and general purpose lighting along the perimeter of buildings, entryways or anywhere extra lighting is needed. For use with 120-277 volt electrical service. ETL Listed for safety and design.



Photocell

97091-SU Photocell



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
87753-SU	LFX/WP/SCT/MW/MV	25/40/60/80	3250/5200/7800/10400	120-277	30K/40K/50K	50000	WL,DIM,DLC	9.2(h) 14.3(w) 7.5(d)
87754-SU	LFX/WP/SCT/HMW/MV	60/80/100/120	7800/10400/13000/15600	120-277	30K/40K/50K	50000	WL,DIM,DLC	9.2(h) 14.3(w) 7.5(d)

Sunlite's LED slim profile wall pack was designed as a maintenance-free, energy-efficient alternative to fluorescent, high-pressure sodium, and metal halide fixtures. It provides uniform illumination while providing a comfortable visual experience. Perfect for outdoor lighting applications, including garages, hotels, commercial buildings, schools, and hospitals. Its die-cast aluminum housing features a bronze finish and polycarbonate lens.

Aluminum Body
Clear Lens
Bronze Finish
70 CRI

Options


- 5 Year Warranty
- Photocell

Application

- Industrial
- Commercial
- Residential

LED Outdoor Wall Mount Series

Cut Off Wall Pack



Photocell

97091-SU Photocell



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
97064-SU	LFX/WP/MW/3SCT	25/40/60/80	3250/5200/7800/10400	120-277	30K/40K/50K	50000	DIM,WL,DLC	8.3(h) 14.4(w) 9.2(d)
97068-SU	LFX/WP/60W/MV/50K	60	7980	120-277	5000K	50000	DIM,WL,DLC	8.3(h) 14.4(w) 9.2(d)
97069-SU	LFX/WP/80W/MV/50K	80	10640	120-277	5000K	50000	DIM,WL,DLC	8.3(h) 14.4(w) 9.2(d)



Aluminum Body
Clear Lens
Black Finish
70 CRI

Options

5 Year Warranty

Photocell

Application

Industrial Commercial Residential

LED Outdoor Wall Mount Series

Rotatable Wall Pack

Sunlite LED Rotatable Wall Pack fixtures are designed to provide ample outdoor illumination with an adjustable light bank allowing you to direct the light for optimal coverage. The weather-resistant aluminum body is finished in black and houses a durable polycarbonate lens. Ideal for security and general purpose lighting along the perimeter of buildings, entryways or anywhere extra lighting is needed. For use with 100-277 volt electrical service. UL Listed for wet location installation and DLC Listed for quality and efficiency.



Rotate 270 Degrees to allow you to customize your range of light



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
97088-SU	LFX/RWP/60W/50K	60	7800	100-277	5000K	50000	WL,DIM,DLC	5.3(h) 8.7(w) 9.2(d)
97095-SU	LFX/RWP/80W/3SCT	80	10000	100-277	30/40k/50K	50000	WL,DIM,DLC	12(h) 11.62(w) 8.0(d)



Aluminum Body
Frosted Lens
Textured Black Finish
80 CRI

5 Year Warranty

Application

Landscape Commercial Residential

LED Outdoor Wall Mount Series

Bulkhead



A Cut-Off



B Round

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	Cut-Off							
81309-SU	LFX/BOF/12W/30K/BK	12	600	120	3000K	50000	WL,DIM	3.6(w) 11.0(d)
B	Round							
81384-SU	LFX/BH/20W/3SCT/BK	20	1000	120	30K/40K/50K	50000	WL,DIM	3.6(w) 11.0(d)

Aluminum Body
Frosted Lens
Bronze Finish
Built-in Photocell
70 CRI

5 Year Warranty Photocell

Application: Industrial, Commercial, Residential

LED Outdoor Wall Mount

Mini Wall Pack



LED BUILT-IN

SWITCH Color Selectable

SWITCH Power Selectable

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
85123-SU	LFX/MWP/MW/SCT/ORB	8/15/25	1120/2050/3250	120-277	30K/40K/50K	50000	WL,DLC	8.2(h) 5.5(w) 3.4(d)

Aluminum Body
Clear Lens
Bronze Finish
Built-in Photocell
80 CRI

5 Year Warranty Photocell

Application: Industrial, Commercial, Residential

LED Outdoor Wall Mount

Mini Wall Pack



LED BUILT-IN

SWITCH Color Selectable

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
85527-SU	LFX/MWP/SCT/15W/PC	15	1800	100-277	30K/40K/50K	50000	WL,DIM	8.6(h) 5.8(w) 3.1(d)

Sunlite LED Slim Wall Pack Fixtures are designed to provide ample outdoor illumination. A built in photocell provides Dusk to Dawn lighting automatically. The weather-resistant steel and aluminum body is finished in black and houses a durable polycarbonate lens. Ideal for security and general purpose lighting along the perimeter of buildings, entryways or anywhere extra lighting is needed. For use outdoors with 120 volt electrical service.

Aluminum Body
White Lens
Black Finish
Built-in Photocell
80 CRI

5 Year Warranty Photocell

Application: Industrial, Commercial, Residential

LED Outdoor Wall Mount

LED Mini Wall Pack



LED BUILT-IN

SWITCH Color Selectable

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
88119-SU	LFX/TP/12W/SCT/PC	12	850	120	30K/40K/50K	50000	WL	8.6(h) 5.3(w) 2.1(d)

Sunlite LED Slim Profile Downlight fixtures are designed to provide ample outdoor illumination. These wall mount fixtures put out a bright 5000K Super White color temperature. An adjustable base allows you to direct the light for optimal coverage. It is an energy-efficient and maintenance-free lighting solution with built-in LEDs with a long life span of up to 50,000 hours. The weather-resistant aluminum body is finished in bronze. Ideal for security and general-purpose lighting along the perimeter of buildings, entryways, or anywhere extra lighting is needed. For use with 120-277 volt electrical service. ETL Listed for wet location installation.

Aluminum Body
Clear Lens
Bronze Finish
70 CRI

Options




Application



LED Outdoor Wall Mount

Adjustable Bracket Down Wall Pack



0-90 Degrees adjustable



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A 49169-SU	LFX/SWP/MW/SCT/BRZ	21/28/35	2730/3640/4550	120-347	30K/40K/50K	50000	WL,DLC	8.1(h) 6.5(w) 3.9(d)
49202-SU	LFX/SWP/HMW/3SCT/BRZ/V2	45/60/75	5850/7800/9750	120-347	30K/40K/50K	50000	WL,DLC	10.9(h) 8.5(w) 4.9(d)
B 49167-SU	LFX/SWP/75W/BZ/50K	75	8625	120-277	5000K	50000	WL,DLC	10.4(h) 9.6(w) 4.3(d)

Sunlite's LED street light fixtures provide ample outdoor illumination and high visibility. They are an energy-efficient solution for your lighting needs. Perfect for commercial, industrial, roadway, parking lot, and pathway lighting. Long life, LED technology built-in means no bulbs to replace and up to 50,000 hours of maintenance-free service. ETL Listed for wet location installation and DLC Listed for quality and efficiency.

Aluminum Body
Clear Lens
Bronze Finish
80 CRI

Options




Application



LED Outdoor Floodlight

Outdoor Area Light



Mounting Hardware

- 85587-SU Slip Fitter Mount Bracket for HMW/SCT Flood Light (85548-SU)
- 85585-SU Slip Fitter Mount Bracket for MMW/SCT Flood Light (85547-SU)
- 85588-SU Trunion Bracket for HMW/SCT Flood Light (85548-SU)
- 85584-SU Trunion Bracket for MW/SCT Flood Light (85546-SU, 85547-SU)
- 85583-SU Knuckle Mount Bracket for MW/SCT Flood Light (85546-SU, 85547-SU)



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	Color Selectable Built-in Photocell							
85548-SU	LFX/FL/HMW/SCT/PC	100/120/150	14000/16800/21000	120-277	30K/40K/50K	50000	WL,DLC,DIM	8.75(h) 11.6(w) 3.85(d)
85547-SU	LFX/FL/MMW/SCT/PC	40/60/80	6300/8400/12000	120-277	30K/40K/50K	50000	WL,DLC,DIM	7.17(h) 9.65(w) 3.07(d)
85546-SU	LFX/FL/MW/SCT/PC	15/25/35	2100/3500/4900	120-277	30K/40K/50K	50000	WL,DLC,DIM	5.43(h) 7.24(w) 2.44(d)
B	Optional Photocell							
85513-SU	LFX/FL/SCT/30W/MV	30	3900	100-277	30K/40K/50K	50000	WL,DIM,DLC	8.0(h) 5.1(w) 1.7(d)

Specifications may change without notice. We are not responsible for any typographical errors



Aluminum Body
Frosted Lens
Black Finish
70 CRI

5 Year Warranty

Application: Landscape, Roadway, Commercial

LED Outdoor Pole-Top Area Light

Decorative Design

Sunlite LED Decorative Acorn Pole-Top Fixtures provide ample lighting for outdoor areas while saving energy. Each dimmable fixture has 50 high output LEDs built-in so there are no bulbs to change. They are designed to mount on 3 inch posts (not included). Ideal for use as street lights, in parking lots, urban areas, parks and more. These commercial grade fixtures feature a frosted black finish on the rust-proof aluminum frame and a frosted polycarbonate diffuser. Both are designed to resist the elements for years of maintenance-free service. They are also ETL Listed for wet location installation and DLC Listed for quality and efficiency.



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
49187-SU	LFX/PTL/MW/SCT	25/40/60/80	3250/5200/7800/10400	120-277	30K/40K/50K	50000	WL,DIM,DLC	40.0(w) 18.0(d)

Sunlite's LED circular pole-top fixtures provide ample lighting for outdoor areas while saving energy. Each dimmable fixture contains 80 high output LEDs that project downward and mount on 3-inch posts (not included). Perfect for parking areas, airports, parks, and more. These commercial grade fixtures feature a frosted bronze finish on the rust-proof aluminum frame and a frosted polycarbonate lens. Both are designed to resist the elements for years of maintenance-free service. They are also UL Listed for wet location installation for quality and efficiency.

Diecast Aluminum Body
Clear Lens
Bronze Finish
80 CRI

Options: 5 Year Warranty, Photocell

Application: Landscape, Roadway, Commercial

LED Outdoor Pole-Top Area Light

Rotatable Design



Photocell

85511-SU	MV 3Pin Photocell W/Receptacle
----------	--------------------------------

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
85525-SU	LFX/PTL/SCT/55W	55	6875	100-277	30K/40K/50K	50000	WL,DIM	20.7(w) 15.0(d)
85526-SU	LFX/PTL/SCT/75W	75	9375	100-277	30K/40K/50K	50000	WL,DIM	20.7(w) 15.0(d)

LED Outdoor Parking Lot Area Light

Roadway Dusk To Dawn



Sunlite's LED Roadway Light Fixtures are designed to save energy while providing ample outdoor lighting for roadways, parking lots, structures, and more. It can be mounted directly to a wall or attached to an arm mount (included). Built-in photocell for automation dusk-to-dawn operation. Uses only 55 watts of electricity while providing as much light as a 250 watt fixture. ETL Listed for wet location installation and DLC Listed for design and quality.

Die-Cast Aluminum Body
Polycarbonate Clear Lens
Dark Bronze Finish
Built-in Photocell
80 CRI



Application



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
49148-SU	LFX/RL/MW/SCT/PC	36/48/60	7500	120-277	30k/40k/50k	50000	WL,DIM,DLC	4.2(h) 7.0(w) 10.4(d)
49149-SU	LFX/RL/HMW/SCT/PC	72/96/120	15000	120-277	30k/40k/50k	50000	WL,DIM,DLC	5.1(h) 9.5(w) 13.5(d)

Sunlite LED Street Light fixtures provide ample outdoor illumination and high visibility. Ideal for commercial, industrial, roadway, parking lot and pathway lighting. Long life, LED technology built-in means no bulbs to replace and up to 50,000 hours of maintenance-free service. ETL Listed for wet location installation and DLC Listed for quality and efficiency.

Metal Body
Clear Lens
Bronze Finish
70 CRI

Options



Application



LED Outdoor Parking Lot Area Light

Outdoor Shoebox Area Light



Mounting Hardware (Low Output)

85331-SU	Trunnion U Bracket
85327-SU	Adjustable Knuckle Mount
85332-SU	Wall Installation Box

Photocell

97091-SU	Photocell
----------	-----------



Mounting Hardware (High Output)

85335-SU	Slip Fitter
85337-SU	Trunnion U Bracket
85336-SU	Non Adjustable Arm
85338-SU	Adjustable Arm



Slip Fitter



Trunnion U Bracket



Non Adjustable Arm



Adjustable Arm



Trunnion Bracket

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	85320-SU LFX/STL/20W/MV/50K/T3	20	2200	120-277	5000K	50000	WL,DLC	2.4(h) 7.3(w) 8.5(d)
B	49174-SU LFX/FL/150W/BRZ/50K	150	18300	120-277	5000K	50000	WL,DLC	7.9(h) 9.5(w) 13.8(d)
C	85323-SU LFX/STL/150W/MV/50K/T3	150	18146	120-277	5000K	50000	WL,DLC	3.6(h) 13.6(w) 18.8(d)

Upgrade your canopy lights and reduce energy costs with LED fixtures from Sunlite. Ideal for gas station canopies, parking structures, underpasses, security lighting, and more. Wide 105 degree beam for optimal coverage and long 50,000 hour lifespan. Designed for outdoor use with weatherproof aluminum base and polycarbonate lens. With no bulbs to replace, this vandal proof fixture is a maintenance-free lighting solution for commercial and industrial applications.

Aluminum & Polycarbonate Body
Clear Lens
Bronze Finish
80 CRI

Options





Application



LED Outdoor Parking Garage Canopy Light

Square



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
88129-SU	LFX/MCM/MW/SCT	30/40/60	3900/5200/7800	120-277	30K/40K/50K	50000	DIM,WL,DLC	10.2(h) 10.2(w)3.4(d)

Cone reflector achieves ideal broad light distribution with low glare



Aluminum & Polycarbonate Body
Clear Lens
Bronze Oxidation Treatment Finish
80 CRI
IP65 Rated Weather Proof




Application



LED Bollard Garden Pathway Series

Exterior Surface



A



B



Mounting Hardware Included

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	87993-SU	12/16/22	2970	120-277	30K/40K/50K	50000	WL,DIM	42.1(h) 6.3(d)
B	87994-SU	12/16/22	2750	120-277	30K/40K/50K	50000	WL,DIM	42.1(h) 6.3(w)

Die-Cast Aluminum Body
Clear Lens
Black Finish
80 CRI

Options



Application



Industrial



Commercial

LED Commercial UFO High Bay


Premium Design



A



B



Polycarbonate Reflector



Polycarbonate Lens



Remote Controller



Microwave Motion & PIR Sensor



Safety Cable

UFO High Bay Accessories

89787-SU	PCR/LFX/HB/V2	Polycarbonate Reflector
89789-SU	PCL/LFX/HB/V2	Polycarbonate Lens
89785-SU	RC/LFX/HB	Remote Controller
89790-SU	SC/LFX/HB	Safety Cable
89699-SU	MS/LFX/HB/V2	Microwave Motion + Daylight Sensor

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A 89780-SU	LFX/HB/100W/50K/V2	100	14000	120-277	5000K	50000	WL,DIM,DLC	(h)4.7 (d)10.7
89781-SU	LFX/HB/150W/50K/V2	150	21000	120-277	5000K	50000	WL,DIM,DLC	(h)4.7 (d)10.7
89782-SU	LFX/HB/200W/50K/V2	200	28000	120-277	5000K	50000	WL,DIM,DLC	(h)5.4 (d)12.5
89783-SU	LFX/HB/240W/50K/V2	240	33600	120-277	5000K	50000	WL,DIM,DLC	(h)5.0 (d)12.5
B 89784-SU	LFX/HB/300W/50K/V2	300	42000	120-277	5000K	50000	WL,DIM,DLC	(h)5.0 (d)12.5

Specifications may change without notice.
We are not responsible for any typographical errors

SUNLITE.COM

CALL 718.768.7000 TOLL-FREE 800.605.BULB

sunlite

High-bay light fixtures illuminate large indoor spaces with high ceilings. Not only do they provide bright and clear lighting from a high position, but they also offer a dependable illumination source. Our high bay light fixtures feature sturdy metal construction and strategically-placed heat dissipation holes on the lamp's surface. This design facilitates a fast heat dissipation process, ensuring the light operates safely and efficiently. Additionally, our linear lights come equipped with a V-shaped hook and hanging chain for easy installation. You can attach the V hook, secure the chain, and complete the wiring without hassle or complications..

LED Commercial Linear High Bay



Linear Design

LED
BUILT-IN



Steel & Acrylic Body
White Lens
White Finish
80 CRI

Options



V Hook Mount & Chain Included

Application



High Bay Accessories

89785-SU RC/LFX/HB Remote Controller
89699-SU MS/LFX/HB/V2 Microwave Motion + Daylight Sensor

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	1 FT							
85280-SU	LFX/HB/1FT/12"/110W/50K	110	14960	120-277	5000K	50000	DL,DIM,DLC	(W) 11.8 (H) 1.57 (D) 15
B	2 FT							
85281-SU	LFX/HB/2FT/12"/165W/50K	165	23000	120-277	5000K	50000	DL,DIM,DLC	(W) 11.97 (H) 1.57 (D) 24
85285-SU	LFX/HB/2FT/14"/220W/50K	220	30000	120-277	5000K	50000	DL,DIM,DLC	(W) 14.15 (H) 1.57 (D) 24

Steel & Acrylic Body
White Lens
White Finish
80 CRI

Options




Application



LED Commercial Linear High Bay

Linear Design

LED
BUILT-IN



V Hook Mount & Chain Included



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
89697-SU	LFX/HB/2'/110W/50K	110	14850	100-277	5000K	50000	DL,DIM,DLC	(W)13.60 (H)2.10 (D) 23.68

LED high-bay lighting fixtures last an average of 50,000 hours and must be replaced at their end of life. Sunlite offers several high-bay replaceable bulbs with various beam-spreads and lumen options. No need for purchasing new fixtures, paying for electricians and lifts to change fixtures, replace the bulb. The initial cost is significantly less than integrated LED fixtures and still assures you proper illumination.

Polycarbonate Body
Mogul (E39) Base
120/277 Volts
Lens & Bulbs Sold Separately

Application



Polycarbonate Lens

04828-SU 16" Lens

04822-SU POLYCARBONATE HIGH BAY REFLECTOR

Commercial Pendants High Bay

HID High Bay

BULB
REQUIRED



Item#	Description	Max Watt	Volt	Light	Features	Dimension(in)
04831-SU	HBFL16PC/P	105	100-277	1	DL	(W)16.02 (H)23.15



120-277 Volts
Mogul Screw (E39)
80 CRI



LED High Lumen Lamps

High Bay Retrofit (Bypass Required)

LED
BUILT-IN



Item#	Description	Watt	Eq. W	Lumen	LPW	CRI	Finish	Kelvin	Hours	MOL(in)	Features	CTN
80871-SU	HBR/LED/60W/E39/50K	60	150	9000	150	80	White	5000K	50000	9.05	DLC	4
80872-SU	HBR/LED/100W/E39/50K	100	250	15000	150	80	White	5000K	50000	12.05	DLC	4
80873-SU	HBR/LED/140W/E39/50K	140	400	20000	143	80	White	5000K	50000	12.13		4



Aluminum Body
Frosted Glass Lens
Gray Finish
80 CRI

5
Year
Warranty

Application



LED VaporProof


Wall Mount & Surface Mount



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
88144-SU	LFX/VT/VTA/21W/3SCT	21	2560	110-277	3000K/4000K/5000K	50000	WL,DIM,DLC	12.6(h) 4.96(w) 4.96(d)


Surface Mount
120 volts
Medium (E26) Base
Uses A19 Bulb
Aluminium Body
UL Listed—Wet Location

Bulb Suggestion





A19
Med E26

Application



Vaporproof

Wall Mount & Surface Mount



Item#	Description	Finish	Lens	Lights	Max Watts	Dimension(in)
A Surface Mount						
41329-SU	VT100 1/2" Pipe	Metallic	Clear Glass	1	100	9.0(w) 4.3(d)
04950-SU	VT200 3/4 Knock Out	Metallic	Clear Glass	1	200	11.6(w) 5.5(d)
B Wall Mount						
41368-SU	VTA100	Metallic	Clear Glass	1	150	7.2(w) 9.5(h) 4.2(d)
Colored Replacement Glass						
C 88150-SU	RPG/LFX/VT/100/B	Blue	Frosted Glass	1	-	6.7(w) 3.4(d)
D 88151-SU	RPG/LFX/VT/100/G	Green	Frosted Glass	1	-	6.7(w) 3.4(d)
E 88152-SU	RPG/LFX/VT/100/R	Red	Frosted Glass	1	-	6.7(w) 3.4(d)
F 88153-SU	RPG/LFX/VT/100/Y	Yellow	Frosted Glass	1	-	6.7(w) 3.4(d)

Aluminum Body
Clear Lens
80 CRI

5
Year
Warranty


Application



A
Foldable Work Light



On / Off
Switch



B
1 Head Work Light

C
2 Head Work Light

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
A	04368-SU LFX/WL/35W/40K	35	35000	120	4000K	50000	DL	8.85(h) 5.7(w) 5.5(d)
B	88176-SU LFX/WL/1H/72W/40K	72	7000	120	4000K	50000	DL	25.4(h) 11.8(w) 5.1(d)
C	88178-SU LFX/WL/2H/144W/40K	144	14000	120	4000K	50000	DL	25.4(h) 11.8(w) 5.1(d)

LED
BUILT-IN

Aluminum & Plastic Body
Cage Lens
Orange Finish
80 CRI

5
Year
Warranty

Application




LED Temporary Construction Work Light

Hanging Mount

LED
BUILT-IN

Linkable



Cable Length:
Standard: 5'
60W Option: 20'
100W Option: 35'
150W Option: 50'



Wire
Guard



Comfort
Latch



On / Off
Remote Control

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
Portable								
85262-SU	LFX/LED/CC/60W/50K/V2	60	7500	120	5000K	50000	DL	12.1(w) 6.9(d)

Sunlite's LED work light boasts a versatile design, catering to a range of tasks including home repairs, car maintenance, camping, and emergency roadside repairs. Its strong magnetic bases ensure a secure attachment to any metal surface. The 360° rotatable heavy-duty plastic hook provides flexibility in positioning the light, and its foldable feature saves space. Adding to its utility, the handle is equipped with a grounded outlet, transforming the work light into an extension cord for corded tools or other electrical needs. Sunlite's LED work light stands out as a practical and convenient tool suitable for a variety of applications.

Plastic Body
COB LED
Built-in Grounded Outlet

Application



Grounded Outlet

LED Construction Work Light

15 FT / 25 FT Power Cord

LED
BUILT-IN



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Cord	Dimension(in)
88179-SU	LFX/PWL/12W/15FT	12	1200	62	6200K	50000	15 FT	17.3(h) 4.7(w) 3.9 (d)
88180-SU	LFX/PWL/12W/25FT	12	1200	62	6200K	50000	25 FT	17.3(h) 4.7(w) 3.9 (d)

120 volts
Medium (E26) Base
Uses A19 Bulb(s)
Plastic Body
ETL Listed

Bulb Suggestion



A19
 Med E26

Application



Construction String Lights

Commercial-Grade

BULB
REQUIRED



Item#	Description	Finish	Gauge	Lights	Max Watts	Dimension
50' Foot						
04223-SU	EX50-14/2/SL	Yellow	14	5	75	50 FT
04224-SU	EX50-16/2/SL	Yellow	16	5	150	50 FT
100' Foot						
04226-SU	EX100-14/2/SL	Yellow	14	10	75	100 FT
04227-SU	EX100-16/2/SL	Yellow	16	10	150	100 FT

Plastic Body
Clear Bulbs
Connect-able Strands
UL Listed

3
Year
Warranty

Application



String Lights with S14 LED Bulbs

Outdoor / Indoor



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
80571-SU	EXT/LED/SL/24'/7S	1.5 x 7	-	120	2700K	25000	DL	24 FT
80572-SU	EXT/LED/SL/48'/15S	1.5 x15	-	120	2700K	25000	DL	48 FT

Sunlite's Emergency Lights provide at least 90 minutes during power outages for residential and commercial. Rechargeable NiCd battery is low maintenance, works on either 120 or 277 volts. Suitable for indoor and damp locations. Designed for use in schools, offices, retail stores, restaurants, and hospitals.

Wall Mount
120/277 volts
Rechargeable NiCd Battery
90 Minutes Illumination
Metal / Plastic Body
UL Listed

Battery Backup

Application



LED Emergency Lights

Wall Mount

LED
BUILT-IN



Item#	Description	Lens	Finish	Lights	Mounting	Dimension(in)
Standard						
A	05268-SU EMER/LED/2H	White Two Head	Plastic	2	Back	4.3(h) 10.1(w) 3.5(d)
B	05269-SU EMER/LED/2H/COM	White Two Head	Plastic	2	Back	3.9(h) 6.3(w) 1.8(d)
NYC Approved						
C	05274-SU EMER/LED/2H/EM/NYC	White Two Head	Metal	2	Back	10.4(h) 14.5(w) 2.2(d)

120/277 volts
 Rechargeable NiCd Battery
 90 Minutes Illumination
 Metal / Thermoplastic Housing
 UL Listed



LED Exit Sign & Emergency Lights Combo


2-in-1 Combo



Application



Optional Third Head Included



New York City Exit signs require red lettering with a height of 8 inches, and the unit must be made of metal or other durable materials.



Item#	Description	Lens	Finish	Lights	Mounting	Dimension(in)
NYC Approved Metal Body						
05275-SU	EXIT/LED/COMBO/1F/2-3H/EM/NYC	White Single Face	Metal	2 or 3	Back	10.4(h) 14.5(w) 2.2(d)



A



B



Item#	Description	Lens	Finish	Lights	Mounting	Dimension(in)	
Thermoplastic Housing							
A	05279-SU	EXIT/LED/R/2H/1-2F/COMBO	White One or Two Face	Thermoplastic	2	Back Top	8.5(h) 11.5(w) 1.75(d)
B	04342-SU	EXIT/1/R/W/RC	White One or Two Face	Thermoplastic	1	Back, Top, Side	9.3(h) 12.6(w) 1.9(d)

120 /277 volts
 Rechargeable NiCd Battery
 90 Minutes Illumination
 UL Listed (Rated Wet Location)




Application



LED Exit Sign

LED
BUILT-IN



Item#	Description	Lens	Finish	Lights	Mounting	Dimension(in)
04362-SU	EXIT/SU/1F/R/WH/WL/EM	One Face	Thermoplastic	1	Back, Top	8.5(h) 12.5(w) 2.5(d)
04344-SU	EXIT/SU/2F/R/WH/WL/EM	Two Face	Metal	1	Back, Top	8.5(h) 12.5(w) 2.5(d)

120 /277 volts
 Rechargeable NiCd Battery
 90 Minutes Illumination
 Metal / Thermoplastic Housing
 UL Listed



Application



LED Exit Sign


LED
BUILT-IN



A
 Metal Housing (Fire Resistant)



B
 Thermoplastic Housing (Fire Resistant)



Item#	Description	Lens	Finish	Lights	Mounting	Dimension(in)
A NYC Approved Metal Housing						
05276-SU	EXIT/LED/1-2F/EM/NYC	One or Two Face	Metal	1	Back, Top, Side	8.5(h) 11.5(w) 1.75(d)
Thermoplastic Housing						
05271-SU	EXIT/LED/R/EM/1-2F	One or Two Face	Thermoplastic	1	Back, Top, Side	8.5(h) 11.5(w) 1.75(d)



120 /277 volts
 Rechargeable NiCd Battery
 90 Minutes Illumination
 UL Listed



Application



Hospitality Office Retail Commercial

LED Exit Sign

Edge Lite



New York City Exit signs require red lettering with a height of 8 inches, and the unit must be made of metal or other durable materials.



Item#	Description	Lens	Finish	Lights	Mounting	Dimension(in)
NYC Approved						
A	05277-SU EXIT/LED/EDGE/SU/1F/WH/CL/EM/NYC	Clear One Face	Acrylic & Metal	1	Top, Side	12.9(h) 15.15(w) 1.65(d)
B	05278-SU EXIT/LED/EDGE/SU/2F/WH/MI/EM/NYC	Mirror Aluminum Two Face	Acrylic & Metal	1	Top, Side	12.9(h) 15.15(w) 1.65(d)

120 /277 volts
 Rechargeable NiCd Battery
 90 Minutes Illumination
 UL Listed



Application



Hospitality Office Retail Commercial

Exit Sign

Edge Lit & Recessed Mount



New York City Exit signs require red lettering with a height of 8 inches, and the unit must be made of metal or other durable materials.



Item#	Description	Lens	Finish	Lights	Mounting	Dimension(in)
NYC Approved						
A	04326-SU EXIT/EDGE/RC/2RF/MI/AL/EM/NYC	Mirror Two Face	Acrylic & Metal	1	Recessed	12.75(h) 16.85(w) 3.25(d)
	04330-SU EXIT/EDGE/RC/1RF/MI/WH/EM/NYC	Mirror One Face	Acrylic & Metal	1	Recessed	12.75(h) 16.85(w) 3.25(d)
B	04325-SU EXIT/EDGE/RC/1RF/CL/AL/EM/NYC	Clear One Face	Acrylic & Metal	1	Recessed	12.75(h) 16.85(w) 3.25(d)

Sunlite's LED light engines allow you to convert your existing light fixtures into state of the art LED fixtures. Take advantage of their high lumen output and energy saving LEDs while producing an even light spread. The Sunlite LED light engines are suitable for most fixtures and are available in a wide range of sizes and color temperatures.

Metal & Plastic Body
Clear Lens
White Finish
90 CRI

3
 Year
 Warranty

Application



LED Flush Mount Circular Module Retrofit Kit

AC Light Engine



3"



4"



5"



6.3"



6.5"

Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
3"								
88458-SU	MODULE/LED/3"/10W/3SCT/AC	10	1000	120	30K/40K/50K	50000	DL,DIM	3.0(d)
88482-SU	MODULE/LED/3"/10W/40K/D/AC	10	700	120	5000K	25000	DL,DIM,ES	0.8(h) 3.3(w) 3.3(d)
88480-SU	MODULE/LED/3"/10W/50K/D/AC	10	700	120	5000K	25000	DL,DIM,ES	0.8(h) 3.3(w) 3.3(d)
4"								
88476-SU	MODULE/LED/4"/17W/5SCT	17	1050	120	27K/30K40K/50K	25000	DL,DIM	0.8(h) 4.4(w) 4.4(d)
5"								
88281-SU	MODULE/LED/5"/20W/SCT/AC	20	2000	120	27K/30K40K/50K/65K	50000	DL,DIM	5.0(d)
6.3"								
88479-SU	MODULE/LED/6.3"/15W/SCT	15	1350	120	30K/40K/50K	50000	DL,DIM	0.55(h) 7.3(w) 7.3(d)
6.5"								
88282-SU	MODULE/LED/6.5"/25W/SCT/AC	25	2500	120	27K/30K40K/50K/65K	50000	DL,DIM	6.5(d)
88283-SU	MODULE/LED/6.5"/30W/SCT/AC	30	3000	120	27K/30K40K/50K/65K	50000	DL,DIM	6.5(d)

Specifications may change without notice.
 We are not responsible for any typographical errors

Plastic Strip
80 CRI

2
Year
Warranty


Application



Bezel Lights

Flexible LED Tape Strip Light

LED
BUILT-IN



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
Single Strips								
80991-SU	BZL/100W/24V/D/30K/1400LED/SINGLE	100	1700	24	3000K	50000	DIM	
80992-SU	BZL/100W/24V/D/40K/1400LED/SINGLE	100	1800	24	4000K-4500K	50000	DIM	
Double Strips								
80987-SU	BZL/140W/24V/D/30K/DOUBLE	140	3000	24	3000K-3500K	50000	DIM	
Triple Strips								
80989-SU	BZL/180W/24V/D/30K/TRIPLE	180	3500	24	3000K-3500K	50000	DIM	
RGB								
80927-SU	BZL/144/12V/D/RGB	144		12	RGB	50000	DIM	



Driver



RGB Touch Controller



Double End No Wire Connector



L Shape Connector



DC Female Jacket Connector



Single Pigtail Wire Connector



Double End Wire Connector



T Shape Connector



X Shape Connector



- 60404-SU
- 60402-SU
- 60400-SU
- 60401-SU

Extrusion

Drivers	
80920-SU	BZL/RGB/RC1
80975-SU	BZL/288W/24V/3-CHANNEL
80972-SU	BZL/120W/24V
80973-SU	BZL/150W/24V
80974-SU	BZL/12-24V/18Amp/3-CHANNEL
80993-SU	BZL/S150W/24V
80994-SU	BZL/S350W/24V
80916-SU	BZL/F100W/12V
80932-SU	BZL/F200W/12V
80970-SU	BZL/DC Female Connector


10mm Connectors	
80979-SU	BZL/BC/SW/10MM
80981-SU	BZL/BC/SW/10MM
80962-SU	BZL/BC/DW/10MM
80980-SU	BZL/BC/10MM
80952-SU	BZL/BC/T/72W/10MM
80976-SU	BZL/BC/L/10MM
80977-SU	BZL/BC/T/10MM
10mm RGB Connectors	
80964-SU	BZL/BC/DW/10MM/RGB
80953-SU	BZL/BC/T/72W/10MM/RGB
80901-SU	BZL/WP/72W/12V/D/W
80909-SU	Rubber Mount For Water Proof

20mm Connectors	
80955-SU	BZL/BC/D/20MM
80963-SU	BZL/BC/DW/20MM
80959-SU	BZL/BC/SW/20MM
20mm RGB Connectors	
80957-SU	BZL/BC/D/20MM/RGB
80961-SU	BZL/BC/SW/20MM/RGB
80965-SU	BZL/BC/DW/20MM/RGB
Extrusions	
60404-SU	AES/6.5'L
60402-SU	AES/6.5'L/0.3D/0.6W
60401-SU	AES/6.5'L/0.6D/0.6W
60400-SU	AES/6.5'L/0.6D/0.6W



Plastic Body
 4 Different Cover Options
 4 Different Color Options
 IP67 Rated
 80 CRI

3
 Year
 Warranty



Scoop	Color
88944-SU SL/SC/BK	Black
88945-SU SL/SC/BN	Brushed Nickel
88946-SU SL/SC/ORB	Oil Rubbed Bronze



Flat	Color
88926-SU SL/FL/BK	Black
88927-SU SL/FL/BN	Brushed Nickel
88928-SU SL/FL/ORB	Oil Rubbed Bronze
88925-SU SL/FL/WH	White



LED Step Light

Outdoor / Indoor



This LED decorative step light is designed to work with a variety of decorative covers for horizontal or vertical mounting. It is IP67 rated and designed to be installed in standard 2x4 single gang boxes.



IP67 Rated Water Resistant

Horizontal Louver	Color
88938-SU SL/HLV/BK	Black
88939-SU SL/HLV/BN	Brushed Nickel
88940-SU SL/HLV/ORB	Oil Rubbed Bronze
88937-SU SL/HLV/WH	White



Vertical Louver	Color
88932-SU SL/VLV/BK	Black
88933-SU SL/VLV/BN	Brushed Nickel
88934-SU SL/VLV/ORB	Oil Rubbed Bronze
88931-SU SL/VLV/WH	White



Item#	Description	Watt	Lumen	Volt	Color Temp	Hours	Features	Dimension(in)
88920-SU	MKS/SL/30K	2	35	120	3000K	25000	WL	4.7(h) 2.9(w) 1.7(d)

120-277 Volts
 80 CRI

Splitter Cable
88186-SU LFL/SC



Refrigerator Display Strip

Wet Rated



Linkable Connector

Item#	Description	Watt	Eq. W	Lumen	LPW	CRI	Lens	Kelvin	Hours	Mol (in)	Features	CTN
Operating environment temperatures from -4 degrees to 104 degrees Fahrenheit (-20 to 40 Celsius)												
88206-SU	SF/FR/LN/48/18/850/MV/WH	18	-	2250	80	82	Clear	5000K	50000	48	DLC, IP65	10
88184-SU	LFX/LFL/22W/MV/50K/5/V2	22	-	2196	100	82	Clear	5000K	50000	59	DLC, IP65	10

Specifications may change without notice.
 We are not responsible for any typographical errors

Replacement Lenses



04387-SU RPG/AM22/WH



04963-SU RPG/AM32/54/CL



04418-SU RPG/AM32/54/WH



04560-SU RPG/B12/WH



04585-SU RPG/D13/AL



04583-SU RPG/D13/FR



04346-SU RPG/DG11/AL



04576-SU RPG/DG11/AL



04573-SU RPG/DG11/CL



04575-SU RPG/DG11/FR



04915-SU RPG/FIX/FM



04939-SU RPG/FIX/SM



04959-SU RPG/FIX/SQ



04953-SU RPG/FIX/VF/CONE



04955-SU RPG/FIX/VF/CYLINDER



04957-SU RPG/FIX/VF/SQUARE



04466-SU RPG/GLO6/AL



04469-SU RPG/GLO6/WH



04480-SU RPG/GLO8/WH



07693-SU RPG/HALL8/WH

Replacement Lenses



05777-SU RPG/LFX/AM/12"
05781-SU RPG/LFX/AM/14"



05780-SU RPG/LFX/DBN13/AL/13"



05779-SU RPG/LFX/DBN13/FR/13"



05784-SU RPG/LFX/DBN15/AL/15"



05783-SU RPG/LFX/DBN15/FR/15"



05775-SU RPG/LFX/DCO12/12"
05785-SU RPG/LFX/DCO16/16"
05787-SU RPG/LFX/DCO18/18"



04382-SU RPG/LFX/DCO32/



05771-SU RPG/LFX/EC/2FT
05797-SU RPG/LFX/EC/2FT
05795-SU RPG/LFX/EC/4FT
05772-SU RPG/LFX/EC/8FT



05776-SU RPG/LFX/HM/12"



05796-SU RPG/LFX/R/GL



05761-SU RPG/LFX/S/GL



A



B



C



D



E

A 88150-SU RPG/LFX/VT/100/B
B 88151-SU RPG/LFX/VT/100/G
C 88152-SU RPG/LFX/VT/100/R
D 88153-SU RPG/LFX/VT/100/Y
E 04526-SU RPG/VT/100/CL
04527-SU RPG/VT/200/CL

Sunshine Lighting
744 Clinton Street
Brooklyn, NY 11231

sunlite

www.sunlite.com

